

GS R3521 Ruglove Barcode Scanner

Metal frame structure

With this delicate design, the PCBA is protected from drops and bumps due to the metal protective frame, which ensures reliable operation. Passed the 1 meter 20,000 times rolling test, the performance is reliable.

Shell material is Hard

The hardness of shell (ABS+PC material) has been greatly improved, is impact-resistant, tensile-resistant, and meets enterprise-grade standards; The imager window (acrylic material) has high strength and strong light transmission.

Scan engine, Zebra SE4107

Bright, rectangular illumination field and LED aiming spot makes scanning more fast and easy. White illumination easily captures color barcodes.

Long battery life

600mAh large-capacity battery, up to 14 hours of use;
The battery can be replaced quickly, and it is equipped with dual-charge and multi-charge chargers;
Up to 16 batteries can be charged at the same time to ensure continuous work in multiple shifts.

Ruglove Wear

Ergonomically designed, it is still comfortable to wear for a long time;
With Ruglove, workers can choose and decide to use left or right hand to work and swap scanning hands on the fly.

Wide applicability

High-quality scanning for printed and mobile barcodes.It can capture virtually any barcode printed on paper labels or displayed on mobile phones;
Support HID, SPP, BLE three transmission protocols;
Support two modes of classic bluetooth and low energy bluetooth;
USB mode supports keyboard and virtual serial port,adapting to various application interfaces.

Application field

The scanner can be widely used in manufacturing, warehousing, logistics, retail and express transportation, and has incomparable advantages in improving production efficiency and accuracy.



ACCESSORIES



Armband
AB1800



Silicone Glove+Trigger

Lycra Glove+Trigger



Bluetooth Dongle
(GS GDA201)



Battery Charger
Dual-slot battery charger
GS GCR201



Battery charger
GS GCR202(eight-slot)/
203(sixteen-slot)

PRODUCT SPECIFICATION

Wearable Barcode Scanner GS R3521

PHYSICAL PARAMETER

Scanner Dimensions	64.9mm(L) × 34.5mm(W) × 24.7mm(D)
Scanner Weight	39.2g(Scanner body)
Battery Capacity	Standard battery: 400mAh; Extended battery: 600mAh
Charging	5V---1A
Charging Time	Standard battery: 400mAh, 80min Extended battery: 600mAh, 100min
Battery Life	400mAh, 8.6h(scan every 5 seconds) 600mAh, 12.9h(scan every 5 seconds)
Notification	LED, Buzzer, Vibration

PERFORMANCE CHARACTERISTICS

Optical Resolution	1280 x 960 pixels
Shutter	Rolling shutter
Sensor	2D CMOS Image
Skew, Pitch & Roll	Skew tolerance: ±60° from normal Pitch tolerance: ±60° from normal Roll tolerance: 360° from normal
Illumination	White LED
Aiming	Green LED
Supported Symbologies	1D: Code39, Code128, Codabar, Code11, UPC/EAN, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Matrix 2 of 5, Korean 3 of 5, GS1 Databar, Code93, MSI, Composite 2D: PDF417, Postal CodesMicro PDF, Micro PDF417, Code128 Emulation, Aztec, Data Matrix, GS1 Data Matrix, QR Code, GS1 QR, Maxicode, Micro QR, Han Xin, Grid Matrix
Interface	USB, Bluetooth
Offline Mode	Support storage of 5000 EAN-13 barcodes

BLUETOOTH

Bluetooth Protocol	HID Keyboard, SPP, and BLE
Bluetooth Range	Communication distance connected to mobile phone > 164.04ft./50m (without obstructions)
Bluetooth OTA	Bluetooth OTA

USB

USB Interface	USB Type-C
USB Protocol	USB HID Keyboard, USB VCP (Virtual Serial Port)
Multilingual Keyboards	USB HID mode supports multilingual keyboards

USER ENVIRONMENT

Ambient Light	Max 107639lux (direct sunlight)
Operating Temperature	-10°C~50°C
Storage Temperature	-10°C~50°C
Humidity	5% - 85% non-condensing
Drop Spec.	Multiple 4.9ft./1.5M drops to concrete
Tumble Spec.	Scanner body withstands 20,000 times from 3.3ft./1M with frequency of 10 times per minute.
Electrostatic	±8kv DC discharge, ±15kv air discharge
Discharge (ESD)	
Certificates	CE, FCC, KC, TELEC, RoHS, ANATEL, NOM, EAC

SOFTWARE SUPPORT

Generalscan Keyboard Pro, Generalscan SDK Demo, Generalscan OTA Tools, Generalscan iCode, G-Service

DECODE RANGES

5 mil Code 39	61 - 241 MM
5 mil Code 128	71 - 229 MM
6.6 milPDF417	61 - 203 MM
10 mil DataMatrix	74 - 216 MM
100% UPC-A	46 - 495 MM
15 mil QR Code	30 - 292 MM
20 mil QR Code	30 - 356 MM

GENERALSCAN

Generalscan Inc.

📍 200 Buckelew Ave, Jamesburg,
NJ 08831, USA
☎ +1 732 895 6821

Generalscan Electronics GmbH

📍 Hochstraße 42, 52525
Heinsberg Germany
☎ +49 1516 7161256

Generalscan LLC

📍 Calle San Luis Potosi 51,
Roma Norte 06700,
Ciudad de México
☎ +52 5552727861

GENERALSCAN ELEKTRONIK VE TEKNOLOJİ SAN. VE TİC. LTD. ŞTİ.

📍 FSM Mah. Siir Sk. Relux Plaza No 10,
Ümraniye 34764,
İstanbul, Turkey
☎ +90 542 478 5873