GAME CHANGER

BIXOLON





MOBILE PRINTERS



Mobile Receipt
Capable of printing receipts and invoices on the go, these compact portable receipt printers are ideal for applications such as proof of delivery, queue busting, and field service. Delivering fast and reliable performance, they provide a convenient printing solution wherever business takes place.



Mobile Label
Designed to print high-quality barcodes, text, images on labels while on the move.These small and rugged Mobile Label printers can be easily transported and used in a variety of applications including shipping, specimen labelling, asset management and more.



Mobile Accessories
Specifically designed to enhance the capability and durability of our printers. BIXOLON's mobile accessories range consists of batteries and chargers to cradles and carrying options, boosting workforce efficiency across all field operations.

LABEL PRINTERS



Desktop Label
BIXOLON’s desktop label printers support printing on 2-inch or 4-inch media with multiple interface options. These space-saving solutions deliver high-quality text, barcode, QR code and logo labelling, offering reliable, cost-effective performance to suit a wide range of business budgets.



Healthcare Label
Built with disinfectant-ready, UV-resistant plastics and an IEC 60601-1 compliant power supply, BIXOLON’s healthcare label printers deliver fast print speeds and high-resolution output for sharp, precise results. Their integrated LCD displays further simplify setup and daily operations.



Industrial Label
BIXOLON’s industrial label printers are designed for high-volume, mission-critical printing in demanding environments. Providing user-centred features such as standalone printing, Twin Functions™ and remote manageability.

POS PRINTERS



Thermal POS
Thermal POS technology is ideal for use in point of sale systems, delivering fast and accurate receipt printing. Designed to handle high transaction volumes, thermal POS printers offer constant performance and user-friendly operations for busy retail and hospitality environments.



Lottery
BIXOLON’s Lottery printer provides dependable, high-quality output supported by advanced sensors that help prevent paper jams. Its wide stacker for easy ticket collection and compact footprint make it an suitable for a variety of gaming environments.



Impact POS
Dot-matrix printers are built to withstand high temperatures, humidity and challenging conditions. They deliver reliable performance in demanding kitchen and retail environments.

LINERLESS PRINTERS



Linerless Thermal POS
BIXOLON’s highly reliable, 2-inch and 3-inch Direct Thermal Linerless POS printers combine high-quality linerless label printing with advanced anti-jamming functionality. Ideal for food order labelling, retail price tags and other fast-paced point-of-sale and hospitality applications.



Linerless Mobile
BIXOLON’s Mobile Receipt and Label Printers with linerless labelling functionality are packed with features making them ideal for a wide range of applications, from shipping and delivery notes to retail, field service, and on-the-go transactions.



Linerless Desktop Label
Exclusively designed for permanent adhesive linerless labelling, BIXOLON’s 4-inch desktop linerless label printers deliver high-quality text, barcode, QR code and logo printing. Supporting various label lengths, they provide efficient, reliable performance for a wide range of retail and logistics applications.

RFID PRINTERS



Mobile RFID
Compact and portable mobile printer supports UHF RFID print and encode technologies on-the-move.



Desktop RFID
Highly reliable, compact Thermal Transfer Desktop RFID label printing solution boosts productivity with mid-volume labelling.



Industrial RFID
BIXOLON’s industrial RFID printer consists of a durable design, full colour LCD display and multi-interface options. Engineered for heavy-duty operations, it delivers reliable, high-performance printing for demanding industrial and logistics applications.

KIOSK PRINTERS



Kiosk Receipt
BIXOLON offers a range of compact, low-profile 2 and 3-inch kiosk receipt printers featuring versatile options including large media roll support, simple drop-in paper loading, blue receipt printing, and optional presenter and retractor functions for flexible deployment.



Kiosk Label
Ideal for various applications in retail, hospitality, and healthcare, BIXOLON's 3 and 4-inch ticket and label kiosk printers provide flexible, reliable performance while supporting a media thickness of up to 0.20 mm for durable high quality printing.





	SPP-C200	SPP-C300
Print Characteristics		
Print Method	Direct Thermal	Direct Thermal
Print Speed	Up to 80 mm/sec	Up to 50 mm/sec
Print Resolution	203 dpi	203 dpi
Print Width	Up to 48 mm	Up to 72 mm
Sensing	Paper End	Paper End
Media Characteristics		
Media Type	Receipt	Receipt
Media Width	58 mm	80 mm
Media Roll Diameter	Up to 40 mm	Up to 50 mm
Media Thickness	0.07 ± 0.005 mm	0.07 ± 0.005 mm
Physical Characteristics		
Dimensions (W x L x H)	79.5 x 115.5 x 45 mm (3.13 x 4.55 x 1.77 inch)	104.4 x 126 x 55.5 mm (4.11 x 4.96 x 2.19 inch)
Weight	Including Battery: 224 g (0.49 lbs.) Paper: 57 g (0.13 lbs.)	Including Battery: 290.5 g (0.64 lbs.) Paper: 133 g (0.29 lbs.)
Power (Nominal Capacity)	EnergyStar® Certified, External AC/DC Battery Charge Battery (3.6 V Li-ion, 3200 mAh, Under 6 Hours Charging Time)	EnergyStar® Certified, External AC/DC Battery Charger Battery (3.6 V Li-ion, 3200 mAh, Under 6 Hours Charging Time)
Performance Characteristics		
Memory	8 MB SDRAM, 4 MB Flash	8 MB SDRAM, 4 MB Flash
Interface	USB 2.0 FS + Bluetooth® Easy Bluetooth Pairing™ via NFC	USB 2.0 FS + Bluetooth® Easy Bluetooth Pairing™ via NFC
Port	Standard: USB Type-C Optional: External Charging 3P	Standard: USB Type-C Optional: External Charging 3P
Environment Characteristics		
Temperature	Operating: -15 to 50°C (5 to 122°F) Storage: -30 to 70°C (-22 to 158°F)	Operating: -15 to 50°C (5 to 122°F) Storage: -30 to 70°C (-22 to 158°F)
Humidity	Operating: 10 to 90% RH	Operating: 10 to 90% RH
Sealing	IP42	IP42
Drop Rate	1.5 m (5 ft.)	1.2 m (4 ft.)
Software		
Emulation	BXL/POS™	BXL/POS™
Driver / Utility	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Utility Program	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Utility Program
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Cordova™ Plugin Web Print SDK (Android/iOS/Windows/macOS) MAUI SDK Flutter™ Plugin React Native® SDK	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Cordova™ Plugin Web Print SDK (Android/iOS/Windows/macOS) MAUI SDK Flutter™ Plugin React Native® SDK
Design & Print	mPrint App (Android/iOS)	mPrint App (Android/iOS)
Fonts / Graphics / Symbologies		
Character Size	Font A: 12 × 24, Font B: 9 × 17, Font C: 9 × 24, KOR, CHN, JPN: 24 × 24	Font A: 12 × 24, Font B: 9 × 17, Font C: 9 × 24, KOR, CHN, JPN: 24 × 24
Characters Per Line	Font A: 32, Font B, C: 42, KOR, CHN, JPN: 16	Font A: 48, Font B, C: 64, KOR, CHN, JPN: 24
Character Sets	Alphanumeric: 95 Expanded Graphics:128×33 Page International: 32	Alphanumeric: 95 Expanded Graphics:128×33 Page International: 32
Barcode Symbologies	1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Aztec, Data Matrix, GS1 Databar, MaxiCode, PDF417, QR Code	1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Aztec, Data Matrix, GS1 Databar, MaxiCode, PDF417, QR Code
Accessories / Supplies / Warranty		
Included in the Box	Belt Clip, USB Cable (A-C,1 m), Battery	Belt Clip, USB Cable (A-C,1 m), Battery
Options & Accessories	USB Cable (C-C,1 m)	USB Cable (C-C,1 m)
Compatible Supplies	-	-
Warranty	2 Years	2 Years







	SPP-R200III	SPP-R310	SPP-R410
Print Characteristics			
Print Method	Direct Thermal	Direct Thermal	Direct Thermal
Print Speed	Up to 100 mm/sec (Receipt) Up to 80 mm/sec (Linerless)	Up to 100 mm/sec (Receipt) Up to 80 mm/sec (Linerless)	Up to 90 mm/sec (Receipt) Up to 60 mm/sec (Linerless)
Print Resolution	203 dpi	203 dpi	203 dpi
Print Width	Up to 48 mm	Up to 72 mm	Up to 104 mm
Sensing	Paper End, Cover Open	Standard: Paper End, Cover Open Optional: Black Mark/Gap	Standard: Paper End, Cover Open Optional: Black Mark/Gap
Media Characteristics			
Media Type	Standard: Receipt, Liner Optional: Linerless	Standard: Receipt, Liner Optional: Linerless	Standard: Receipt, Liner Optional: Linerless
Media Width	Standard: 58 mm Optional: Partition 50 mm	80 mm	Standard: 112 mm Optional: Partition 105 mm
Media Roll Diameter	Up to 40 mm	Up to 50 mm	Up to 57 mm
Media Thickness	0.07 ± 0.005 mm	0.07 ± 0.005 mm	0.07 ± 0.005 mm
Physical Characteristics			
Dimensions (W x L x H)	79.5 x 124.5 x 44.1 mm (3.13 x 4.9 x 1.74 inch)	105 x 126 x 58 mm (4.14 x 4.97 x 2.29 inch)	143 x 138 x 66 mm (5.63 x 5.44 x 2.60 inch)
Weight	Including Battery: 228 g (0.50 lbs.) Including MSR: 238 g (0.52 lbs.)	Including Battery: 385 g (0.85 lbs.) Including MSR: 405 g (0.9 lbs.) Paper: 133 g (0.29 lbs.)	Including Battery: 530 g (1.17 lbs.) Paper: 242 g (0.53 lbs.)
Power (Nominal Capacity)	EnergyStar® Certified, External AC/DC Battery Charger SPP-R200III: Battery (7.4 V Li-ion, 1200 mAh, Under 2.5 Hours Charging Time)	EnergyStar® Certified, External AC/DC Battery Charger SPP-R310: Battery (7.2 V Li-ion, 3200 mAh, Under 4 Hours Charging Time)	EnergyStar® Certified, External AC/DC Battery Charger Battery (7.2 V Li-ion, 3200 mAh, Under 4 Hours Charging Time)
Performance Characteristics			
Memory	8 MB SDRAM, 4 MB Flash	8 MB SDRAM, 4 MB Flash	8 MB SDRAM, 4 MB Flash
Interface	SPP-R200III Standard: USB 2.0 FS + Serial Optional: ① USB 2.0 FS + Serial + Bluetooth® ② USB 2.0 FS + Serial + WLAN WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) Easy Bluetooth Pairing™ via NFC	SPP-R310 Standard: USB 2.0 FS + Serial Optional: ① USB 2.0 FS + Serial + Bluetooth® ② USB 2.0 FS + Serial + WLAN WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) Easy Bluetooth Pairing™ via NFC	Standard: USB 2.0 FS + Serial Optional: ① USB 2.0 FS + Serial + Bluetooth® ② USB 2.0 FS + Serial + WLAN WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) Easy Bluetooth Pairing™ via NFC
Port	SPP-R200III:Power, Serial/USB 14P	SPP-R310: Power, Serial/USB 14P	Power Serial/USB 14P
Environment Characteristics			
Temperature	Operating: -15 ~ 50°C (5 ~ 122°F) Storage: -30 ~ 70°C (-22 ~ 158°F)	Operating: -15 to 50°C (5 to 122°F) Storage: -30 to 70°C (-22 to 158°F)	Operating: -15 to 50°C (5 to 122°F) Storage: -30 to 70°C (-22 to 158°F)
Humidity	Operating: 10 to 90% RH	Operating: 10 to 90% RH	Operating: 10 to 90% RH
Sealing	IP43 (IP54 with Protective Case)	IP54	IP54
Drop Rate	2.1 m (7 ft.)/1.5 m (5 ft.) for MSR Model	1.8 m (6 ft.)	1.8 m (6 ft.)
Software			
Emulation	BXL/POS™	BXL/POS™	BXL/POS™
Driver / Utility	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Utility Program Network Auto Installer	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Utility Program Network Auto Installer	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Utility Program Network Auto Installer
Developer Tools	Android™/iOS®/Windows SDK, Linux SDK, Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS), Cordova™ Plugin, MAUI SDK, Flutter™ Plugin, React Native® SDK	Android™/iOS®/Windows SDK, Linux SDK, Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS), Cordova™ Plugin, MAUI SDK, Flutter™ Plugin, React Native® SDK	Android™/iOS®/Windows SDK, Linux SDK, Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS), Cordova™ Plugin, MAUI SDK, Flutter™ Plugin, React Native® SDK
Design & Print	mPrint App (Android/iOS)	mPrint App (Android/iOS)	mPrint App (Android/iOS)
Fonts / Graphics / Symbologies			
Character Size	Font A: 12 × 24, Font B: 9 × 17, Font C: 9 × 24, KOR, CHN, JPN: 24 × 24	Font A: 12 × 24, Font B: 9 × 17, Font C: 9 × 24, KOR, CHN, JPN: 24 × 24	Font A: 12 × 24, Font B: 9 × 17, Font C: 9 × 24, KOR, CHN, JPN: 24 × 24
Characters Per Line	Font A: 32, Font B, C: 42, KOR, CHN, JPN: 16	Font A: 48, Font B, C: 64, KOR, CHN, JPN: 24	Font A: 69, Font B, C: 92, KOR, CHN, JPN: 34
Character Sets	Alphanumeric: 95 Expanded Graphics: 128 × 33 Page International: 32 Optional Unicode Supported (UTF-8, UTF-16LE, UTF-16BE)	Alphanumeric: 95 Expanded Graphics: 128 × 33 Page International: 32 Optional Unicode Supported (UTF-8, UTF-16LE, UTF-16BE)	Alphanumeric: 95 Expanded Graphics: 128 × 33 Page International: 32 Optional Unicode Supported (UTF-8, UTF-16LE, UTF-16BE)
Barcode Symbologies	1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Aztec, Data Matrix, GS1 Databar, MaxiCode, PDF417, QR Code	1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Aztec, Data Matrix, GS1 Databar, MaxiCode, PDF417, QR Code	1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Aztec, Data Matrix, GS1 Databar, MaxiCode, PDF417, QR Code
Accessories / Supplies / Warranty			
Included in the Box	Belt Clip, Battery, AC/DC Battery Charger, Power Cord, Paper	Belt Clip, Battery, AC/DC Battery Charger, Power Cord, Paper	Belt Clip, Battery, AC/DC Battery Charger, Power Cord, Paper
Options & Accessories	Belt/Shoulder Strap, Soft/Protective Case, Battery, USB Charger, AC/DC PD Adapter (SPP-R200IIIU), Power Cord, Single/Quad Battery Charger, Single/Quad Docking Cradle, Vehicle Charger, Vehicle Holder, Serial Cable (D-Sub 9P(M)-14P,1 m), USB Cable (A-14P,1 m), Protective Jacket, Battery Clip	Belt/Shoulder Strap, Soft/Protective Case, USB Charger (SPP-R310), Single Battery Cradle, Quad Battery Charger, Vehicle Charger (SPP-R310), RAM Mount Vehicle Holder, Vehicle Holder, Serial Cable (D-Sub 9P(M)-14P,1 m) (SPP-R310), USB Cable (A-14P,1 m) (SPP-R310)	Belt/Shoulder Strap, Soft Case, USB Charger, Single Battery Cradle, Quad Battery Charger, Vehicle Charger, RAM Mount Vehicle Holder, Vehicle Holder, Serial Cable (D-Sub 9P(M)-14P,1 m), USB Cable (A-14P,1 m)
Compatible Supplies	B-linerless™	B-linerless™	B-linerless™
Warranty	2 Years	2 Years	2 Years
Integrated Card Reader (Optional)			
MSR	3 Track (T-DES/DUKPT (Optional))	3 Track (T-DES/DUKPT (Optional))	-





	SPP-L310	SPP-L410
Print Characteristics		
Print Method	Direct Thermal	Direct Thermal
Print Speed	Up to 5 ips (127 mm/sec)	Up to 4 ips (102 mm/sec)
Print Resolution	203 dpi	203 dpi
Print Width	Up to 72 mm	Up to 104 mm
Sensing	Paper End Gap Black Mark Cover Open	Paper End Gap Black Mark Cover Open
Media Characteristics		
Media Type	Standard: Liner Optional: Linerless	Standard: Liner Optional: Linerless
Media Width	Standard: 80 mm Optional: Detachable 58/62/66/70/74 mm, Partition 38/58 mm	Standard: 112 mm Optional: Partition 80/105 mm
Media Roll Diameter	Up to 49 mm	Up to 56 mm
Media Thickness	0.07 to 0.19 mm	0.07 to 0.19 mm
Media Inner Core	-	-
Physical Characteristics		
Dimensions (WxLxH)	105 x 126 x 58 mm (4.14 x 4.97 x 2.29 inch)	143 x 138 x 66 mm (5.63 x 5.44 x 2.60 inch)
Weight	Including Battery: 385 g (0.85 lbs.) Paper: 133 g (0.29 lbs.)	Including Battery: 530 g (1.17 lbs.) Paper: 242 g (0.53 lbs.)
Power (Nominal Capacity)	EnergyStar® Certified, External AC/DC Battery Charger Battery (7.2 V Li-ion, 3200 mAh, Under 4 Hours Charging Time)	EnergyStar® Certified, External AC/DC Battery Charger Battery (7.2 V Li-ion, 3200 mAh, Under 4 Hours Charging Time)
Peeler	-	-
Display	-	-
Performance Characteristics		
Memory	Standard: 128 MB SDRAM, 256 MB Flash Optional: 256 MB SDRAM, 512 MB Flash	Standard: 128 MB SDRAM, 256 MB Flash Optional: 256 MB SDRAM, 512 MB Flash
Interface	Standard: USB 2.0 HS + Serial Optional: ① USB 2.0 FS + Serial + Bluetooth® ② USB 2.0 FS + Serial + WLAN WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) Easy Bluetooth Pairing™ via NFC	Standard: USB 2.0 HS + Serial Optional: ① USB 2.0 FS + Serial + Bluetooth® ② USB 2.0 FS + Serial + WLAN WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) Easy Bluetooth Pairing™ via NFC
Port	Power Serial/USB 14P	Power Serial/USB 14P
Environment Characteristics		
Temperature	Operating: -15 to 50°C (5 to 122°F) Storage: -30 to 70°C (-22 to 158°F)	Operating: -15 to 50°C (5 to 122°F) Storage: -30 to 70°C (-22 to 158°F)
Humidity	Operating: 10 to 90% RH	Operating: 10 to 90% RH
Sealing	IP54	IP54
Drop Rate	1.8 m (6 ft.)	1.8 m (6 ft.)
Software		
Emulation	SLCS™, BPL-Z™ (ZPL II®), BPL-C™ (CPCL)	SLCS™, BPL-Z™ (ZPL II®), BPL-C™ (CPCL)
Driver/Utility	Windows® Driver (Europlus/Seagull) Linux®/macOS® CUPS Driver Virtual COM USB Driver Utility Program OPOS/JPOS Driver Device Driver for SAP® Network Auto Installer	Windows® Driver (Europlus/Seagull) Linux®/macOS® CUPS Driver Virtual COM USB Driver Utility Program OPOS/JPOS Driver Device Driver for SAP® Network Auto Installer
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK
Design & Print	Label Artist-II™ Label Artist™ Web Label Artist™ Mobile (Android/iOS) mPrint App (Android/iOS) BarTender® Ultralite for BIXOLON	Label Artist-II™ Label Artist™ Web Label Artist™ Mobile (Android/iOS) mPrint App (Android/iOS) BarTender® Ultralite for BIXOLON
MDM(Optional)	-	Label Artist-II™ Poo Label Artist™ Web Label Artist™ Mobile (Android/iOS) mPrint App (Android/iOS) BarTender® Ultralite for BIXOLON
Fonts / Graphics / Symbologies		
Fonts	Bitmap Fonts (10 SLCS, 16 BPL-Z, 7 BPL-C), Scalable Fonts (1 SLCS, 1 BPL-Z) 23 Code Page, Unicode (UTF-8, UTF-16LE, UTF-16BE)	Bitmap Fonts (10 SLCS, 16 BPL-Z, 7 BPL-C), Scalable Fonts (1 SLCS, 1 BPL-Z) 23 Code Page, Unicode (UTF-8, UTF-16LE, UTF-16BE)
Downloadable Objects	Supporting User-Defined Fonts (TTF, TTE, FNT, CSF, CPF), Graphics, Formats, Layouts and Logos	Supporting User-Defined Fonts (TTF, TTE, FNT, CSF, CPF), Graphics, Formats, Layouts and Logos
Barcode Symbologies	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN Extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, TLC 39	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN Extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, TLC 39
Accessories / Supplies / Warranty		
Included in the Box	Belt Clip, Battery, AC/DC Battery Charger, Power Cord	Belt Clip, Battery, AC/DC Battery Charger, Power Cord
Options & Accessories	Belt/Shoulder Strap,Soft/Protective Case,USB Charger, Single Battery Cradle, Quad Battery Charger, Vehicle Charger, RAM Mount Vehicle Holder, Serial Cable (D-Sub 9P(M)-14P,1 m), USB Cable (A-14P,1 m), Detachable Media Holder	Belt/Shoulder Strap, Soft Case, USB Charger,Single Battery Cradle, Quad Battery Charger, Vehicle Charger, RAM Mount Vehicle Holder, Serial Cable (D-Sub 9P(M)-14P,1 m), USB Cable (A-14P,1 m)
Compatible Supplies	B-linerless™	B-linerless™
Warranty	2 Years	2 Years


XM7-20


XM7-30


XM7-40


XM7-40R

	XM7 Series
Print Characteristics	
Print Method	Direct Thermal
Print Speed	XM7-20: Up to 6 ips (152 mm/sec) XM7-30, XM7-40: Up to 5 ips (127 mm/sec)
Print Resolution	203 dpi
Print Width	XM7-20: Up to 48 mm XM7-30: Up to 72 mm XM7-40: Up to 104 mm
Sensing	Paper End Gap Black Mark Cover Open Peel-off
Media Characteristics	
Media Type	Standard: Liner, Notch Optional: Linerless, RFID Tag (XM7-40R only)
Media Width	XM7-20: 25 to 58 mm XM7-30: 25 to 80 mm XM7-40: 50 to 112 mm
Media Roll Diameter	XM7-20: Up to 57 mm XM7-30, XM7-40: Up to 66 mm
Media Thickness	0.07 to 0.19 mm
Media Inner Core	19 mm, 12 mm
Physical Characteristics	
Dimensions (WxLxH)	XM7-20: 93 x 168 x 69 mm 3.66 x 6.61 x 2.72 inch) XM7-30: 119 x 180 x 79 mm (4.69 x 7.09 x 3.12 inch) XM7-40: 158 x 186 x 82 mm (6.23 x 7.33 x 3.23 inch)
Weight	XM7-20: Including Battery: 600 g (1.32 lbs.) Paper: 120g (0.26 lbs.) XM7-30: Including Battery: 795 g (1.76 lbs.) Paper: 260 g (0.58 lbs.) XM7-40: Including Battery: 1,100 (2.43 lbs) XM7-40R: Including Battery: 1,130 g (2.50 lbs), Paper: 360 g (0.79 lbs)
Power (Nominal Capacity)	EnergyStar® Certified, External AC/DC Adapter, USB Type-C® Power Delivery Charging (Sink) Support XM7-20: Battery (7.2V Li-ion, 3200 mAh, Under 3 Hours Charging Time) Optional: Smart Battery (7.2 V Li-ion, 3400 mAh, Under 3 Hours Charging Time) XM7-30: Smart Battery (7.2 V Li-ion, 3400 mAh, Under 3 Hours Charging Time) Optional: Battery (7.2V Li-ion, 3200 mAh, Under 3 Hours Charging Time) XM7-40: Smart Battery (7.2V Li-ion, 6800 mAh, Under 6 Hours Charging Time)
Peeler	Supported
Display	TFT LCD (IPS, 240 x 320 pixels)
Performance Characteristics	
Memory	Standard: 128 MB SDRAM, 256 MB Flash Optional: 256 MB SDRAM, 512 MB Flash
Interface	Standard: USB 2.0 HS + Serial Optional: ① USB 2.0 HS + Serial + Bluetooth® ② USB 2.0 FS + Serial + WLAN ③ USB 2.0 FS + Serial + Bluetooth + WLAN XM7-40R: USB 2.0 HS + Serial + Bluetooth + WLAN WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) Easy Bluetooth Pairing™ via NFC
Port	Power USB Type-C Serial/USB 14P External Charging/Ethernet 12P
Environment Characteristics	
Temperature	Operating: -15 to 50°C (5 to 122°F) Storage: -30 to 70°C (-22 to 158°F)
Humidity	Operating: 10 to 90% RH
Sealing	IP54
Drop Rate	XM7-20, XM7-30: 2.1 m (7 ft.) XM7-40: 1.8 m (6 ft.)
Software	
Emulation	SLCS™, BPL-Z™ (ZPL II®), BPL-C™ (CPCL), BXL/POS™ XM7-40R: SLCS™, BPL-Z™ (ZPL II®)
Driver/Utility	Windows® Driver (Europlus/Seagull) Linux®/macOS® CUPS Driver Virtual COM USB Driver Utility Program OPOS/JPOS Driver Device Driver for SAP® Network Auto Installer
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK
Design & Print	Label Artist-II™ Label Artist™ Web Label Artist™ Mobile (Android/iOS) mPrint App (Android/iOS) BarTender® Ultralite for BIXOLON
MDM(Optional)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android) SOTI® Connect Supported
Fonts / Graphics / Symbologies	
Fonts	Bitmap Fonts (10 SLCS, 16 BPL-Z, 7 BPL-C), Scalable Fonts (1 SLCS, 1 BPL-Z) 23 Code Page, Unicode (UTF-8, UTF-16LE, UTF-16BE)
Downloadable Objects	Supporting User-Defined Fonts (TTF, TTE, FNT, CSF, CPF), Graphics, Formats, Layouts and Logos
Barcode Symbologies	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN Extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, TLC 39
Accessories / Supplies / Warranty	
Included in the Box	Belt Strap, Battery (XM7-20), Smart Battery (XM7-30, XM7-40), AC/DC Adapter, Power Cord, Media Disks (Inner Core: 12 mm)
Options & Accessories	Soft Case, Shoulder Strap, Battery, Smart Battery, AC/DC PD Adapter, Single/Quad Battery Charger, Single/Quad Docking Cradle (Optional Ethernet), Vehicle Adapter, RAM Mount Vehicle Holder, Serial Cable (Optional Fixed) (D-Sub 9P(M)-14P,1 m), USB Cable (Optional Fixed) (A-14P, 1 m), USB Cable (A-C,1 m / C-C, 1 m)
Compatible Supplies	B-linerless™
Warranty	2 Years
RFID (XM7-40R only)	
Frequency	UHF, 865 to 928 MHz
Transmit Power	1 W
Modulation	ASK
Protocol	ISO 18000-63 (EPC Class1 Gen2V2)
Tag Pitch	Min 16 mm



SLP-DL410



SLP-DL410KV



XD3-40d

NEW



XD3-40d-H



XD3-40t

	SLP-DL410 Series	XD3-40 Series
Print Characteristics		
Print Method	Direct Thermal	XD3-40d: Direct Thermal XD3-40t: Thermal Transfer or Direct Thermal
Print Speed	Up to 5 ips (127 mm/sec)	Up to 5 ips (127 mm/sec)
Print Resolution	SLP-DL410: 203 dpi SLP-DL413: 300 dpi	203 dpi
Print Width	SLP-DL410: Up to 108 mm SLP-DL413: Up to 105.7 mm	Up to 104 mm
Print Length	Up to 2,000 mm	Up to 1,000 mm
Sensor	Transmissive, Reflective (Adjustable), Head Open	Transmissive (Fixed), Reflective (Adjustable), Head Open, Ribbon-End (XD3-40t only)
Media Characteristics		
Media Type	Gap, Black Mark, Notch, Continuous, Fan-Fold	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	25 to 116 mm	15 to 118 mm
Media Roll Diameter	External roll media options up to 150 mm to 205 mm	Up to 127 mm
Media Thickness	0.06 to 0.20 mm	0.06 to 0.20mm
Supply Method	-	Easy Paper Loading
Inner Core	-	25.4 to 38.1 mm
Ribbon Characteristics		
Ribbon Type	-	Wax, Wax/Resin, Resin, Outside
Ribbon Width	-	33 to 110 mm
Ribbon Length	-	Up to 300 m
Core Inner Diameter	-	25.4 mm, 12.7 mm
Physical Characteristics		
Dimensions (W x L x H)	177 x 150 x 148.5 mm (6.97 x 5.91 x 5.85 inch)	XD3-40d: 181 x 222 x 168 mm (7.13 x 8.74 x 6.62 inch) XD3-40t: 210 x 284 x 186 mm (8.3 x 11.2 x 7.3 inch)
Weight	1.6 kg (3.53 lbs.) SLP-DL410KV: 1.73 kg (3.81 lbs.)	XD3-40d: 1.7 kg (3.75 lbs.) XD3-40t: 2.6 kg (5.73 lbs.)
Electrical	EnergyStar® Certified, Internal Power Adapter 100-240 VAC, 50/60 Hz SLP-DL410KV: Internal Power Converter, Input DC12 V 6.0 A, Output DC24 V 2.5 A, LPC-4000)	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz
Performance Characteristics		
Memory	64 MB SDRAM, 128 MB Flash	64 MB SDRAM, 128 MB Flash
Interface	Standard: USB + USB Host Optional: ① USB + USB Host + Ethernet ② USB + USB Host + Ethernet + Bluetooth® ③ USB + USB Host + Bluetooth * Compatible with WLAN Dongle(802.11a/b/g/n/ac) via a USB Host Port	Standard: USB Optional: USB + Serial + Ethernet
Real Time Clock	Supported (Optional)	-
Environment Characteristics		
Temperature	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 5 to 95% RH	Operating: 10 to 80% RH Storage: 5 to 95% RH
Software		
Emulation	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL, Optional)	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL, Optional)
Driver / Utility	Windows® Driver (Europlus/Seagull) Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program OPOS/JPOS Driver Device Driver for SAP® Network Auto Installer	Windows® Driver (Europlus/Seagull) Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program OPOS/JPOS Driver Device Driver for SAP® Network Auto Installer
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK	Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK
Design & Print	Label Artist-II™ Label Artist™ Web Label Artist™ Mobile (Android/iOS) mPrint App (Android/iOS) BarTender® Ultralite for BIXOLON	Label Artist-II™ Label Artist™ Web BarTender® Ultralite for BIXOLON
MDM (Optional)	SOTI® Connect supported	-
Fonts / Graphics / Symbologies		
Fonts	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E), Scalable Fonts (1 SLCS, 1 BPL-Z), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E, 9 BPL-D), Scalable Fonts (1 SLCS, 1 BPL-Z, 1 BPL-D), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)
Downloadable Objects	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos
Barcode Symbologies	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39
Accessories / Supplies / Warranty		
Included in the Box	AC/DC Adapter, Power Cord, USB Cable SLP-DL410KV: Cigar Jack Cable	AC/DC Adapter, Power Cord, USB Cable XD3-40t: Holder Ribbon x 2, Core Paper (0.5-inch, 1-inch)
Options & Accessories	Peeler, Auto Cutter, External Paper Supply, External Power Adapter (Not for SLP-DL410KV), WLAN Dongle (Consensus required), USB Cable	Peeler, External Paper Supply, Serial Cable
Compatible Supplies	-	B-ribbon™, B-band™
Warranty	3 Years	3 Years





	SLP-DX220	SLP-TX220
Print Characteristics		
Print Method	Direct Thermal	Thermal Transfer or Direct Thermal
Print Speed	SLP-DX220: Up to 6 ips (152 mm/sec) SLP-DX223: Up to 4 ips (100 mm/sec)	SLP-TX220: Up to 6 ips (152 mm/sec) SLP-TX223: Up to 4 ips (100 mm/sec)
Print Resolution	SLP-DX220: 203 dpi SLP-DX223: 300 dpi	SLP-TX220: 203 dpi SLP-TX223: 300 dpi
Print Width	SLP-DX220: Up to 54 mm SLP-DX223: Up to 56.9 mm	SLP-TX220: Up to 54 mm SLP-TX223: Up to 56.9 mm
Print Length	Up to 2,000 mm	Up to 2,000 mm
Sensor	Transmissive, Reflective (Adjustable), Head Open	Transmissive, Reflective (Adjustable), Head Open
Media Characteristics		
Media Type	Gap, Black Mark, Notch, Continuous, Fan-Fold	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	Standard: 15 to 60 mm Peeler: 15 to 58 mm	15 to 60 mm
Media Roll Diameter	Up to 130 mm	Up to 130 mm
Media Thickness	0.06 to 0.20 mm	0.06 to 0.20 mm
Supply Method	Easy Paper Loading	Easy Paper Loading
Inner Core	12.5 to 38.1 mm	12.5 to 38.1 mm
Ribbon Characteristics		
Ribbon Type	-	Wax, Wax/Resin, Resin, Outside
Ribbon Width	-	58 mm
Ribbon Length	-	Up to 74 m
Core Inner Diameter	-	12.7 mm
Physical Characteristics		
Dimensions (W x L x H)	120 x 230 x 170 mm (4.72 x 9.05 x 6.69 inch)	144 x 252 x 173 mm (5.67 x 9.92 x 6.81 inch)
Weight	1.36 kg (2.99 lbs.)	1.71 kg (3.77 lbs.)
Electrical	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz
Performance Characteristics		
Memory	64 MB SDRAM, 128 MB Flash SLP-DX220W (WLAN) Optional: 256 MB SDRAM, 512 MB Flash	64 MB SDRAM, 128 MB Flash
Interface	Standard: USB + Serial Optional: ① USB + Ethernet + USB Host ② USB + USB Host + Bluetooth® ③ USB + USB Host + WLAN * WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP)	Standard: USB + Serial Optional: ① USB + Ethernet + USB Host ② USB + USB Host + Bluetooth® * Compatible with WLAN Dongle(802.11a/b/g/n/ac) via a USB Host Port
Real Time Clock	Supported (Optional)	Supported (Optional)
Environment Characteristics		
Temperature	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 5 to 95% RH	Operating: 10 to 80% RH Storage: 5 to 95% RH
Software		
Emulation	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL, Optional)	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL, Optional)
Driver / Utility	Windows® Driver (Europlus/Seagull), Linux®/macOS® CUPS Driver, Virtual COM USB/Ethernet Driver, Utility Program, OPOS/JPOS Driver, Device Driver for SAP®, Network Auto Installer	Windows® Driver (Europlus/Seagull), Linux®/macOS® CUPS Driver, Virtual COM USB/Ethernet Driver, Utility Program, OPOS/JPOS Driver, Device Driver for SAP®, Network Auto Installer
Developer Tools	Android™/iOS®/Windows SDK, Linux SDK, Xamarin® SDK, Web Print SDK (Android/iOS/Windows/macOS), Cordova™ Plugin, MAUI SDK, Flutter™ Plugin, React Native® SDK	Android™/iOS®/Windows SDK, Linux SDK, Xamarin® SDK, Web Print SDK (Android/iOS/Windows/macOS), Cordova™ Plugin, MAUI SDK, Flutter™ Plugin, React Native® SDK
Design & Print	Label Artist-II™, Label Artist™ Web, Label Artist™ Mobile (Android/iOS), mPrint App (Android/iOS), BarTender® Ultralite for BIXOLON	Label Artist-II™, Label Artist™ Web, Label Artist™ Mobile (Android/iOS), mPrint App (Android/iOS), BarTender® Ultralite for BIXOLON
MDM (Optional)	SOTI® Connect supported	SOTI® Connect supported
Fonts / Graphics / Symbologies		
Fonts	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E), Scalable Fonts (1 SLCS, 1 BPL-Z), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E), Scalable Fonts (1 SLCS, 1 BPL-Z), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)
Downloadable Objects	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos
Barcode Symbologies	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39
Accessories / Supplies / Warranty		
Included in the Box	AC/DC Adapter, Power Cord, USB Cable	AC/DC Adapter, Power Cord, USB Cable,Core Paper (0.5-inch)
Options & Accessories	Peeler, Auto Cutter, Serial Cable	Peeler, Auto Cutter, External Paper Supply, WLAN Dongle (Consensus required), Serial Cable
Compatible Supplies	-	B-ribbon™, B-band™
Warranty	3 Years	3 Years



XD5-40d XD5-40t XD5-40tR

XD5-40 Series

Print Characteristics	
Print Method	XD5-40d: Direct Thermal XD5-40t: Thermal Transfer or Direct Thermal
Print Speed	XD5-40d: Up to 7 ips (178 mm/sec) XD5-43d: Up to 5 ips (127 mm/sec) XD5-40t: Up to 6 ips (152 mm/sec) XD5-43t: Up to 4 ips (102 mm/sec)
Print Resolution	XD5-40: 203 dpi XD5-43: 300 dpi
Print Width	XD5-40: Up to 108 mm XD5-43: Up to 105.7 mm
Print Length	Up to 1,000 mm
Sensor	Transmissive (Fixed), Reflective (Adjustable), Head Open, Ribbon-End (XD5-40t / XD5-40tR only)
Media Characteristics	
Media Type	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	15 to 118 mm
Media Roll Diameter	Up to 127 mm
Media Thickness	0.06 to 0.20 mm
Supply Method	Easy Paper Loading
Inner Core	25.4 to 38.1 mm
Ribbon Characteristics	
Ribbon Type	Wax, Wax/Resin, Resin, Outside
Ribbon Width	33 to 110 mm
Ribbon Length	Up to 300 m
Core Inner Diameter	25.4 mm, 12.7 mm
Physical Characteristics	
Dimensions (W x L x H)	XD5-40d: 194 x 248 x 169 mm (7.64 x 9.76 x 6.65 inch) XD5-40t: 210 x 284 x 188 mm (8.3 x 11.2 x 7.4 inch)
Weight	XD5-40d: 1.89 kg (4.17 lbs.) XD5-40t: 2.48 kg (5.46 lbs.)
Electrical	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz
Display	XD5-40d & XD5-40t Standard: None Optional: FSTN LCD (200 x 100 pixels) XD5-40tR Standard: FSTN LCD (200 x 100 pixels)
Performance Characteristics	
Memory	Standard: 64 MB SDRAM, 128 MB Flash Optional: ① 256 MB SDRAM, 256 MB Flash ② 256 MB SDRAM, 512 MB Flash XD5-40tR Standard: 256 MB SDRAM, 256 MB Flash
Interface	Standard: USB + USB Host Optional: ① USB + USB Host + Serial+Ethernet ② USB + USB Host + Serial + Ethernet + WLAN ③ USB + USB Host + Serial + Ethernet + Bluetooth® XD5-40tR Standard: USB + USB Host + Serial + Ethernet Optional: ① USB + USB Host + Serial + Ethernet + WLAN ② USB + USB Host + Serial + Ethernet + Bluetooth WLAN: 2.4G/5GHz, 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) Ethernet: 10/100Mbps
Real Time Clock	Supported (Optional)
Environment Characteristics	
Temperature	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 5 to 95% RH
Software	
Emulation	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL, Optional), XML(Optional)
Driver / Utility	Windows® Driver (Europlus/Seagull) Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program OPOS/JPOS Driver Device Driver for SAP® Network Auto Installer
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) XI (Optional) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK
Design & Print	Label Artist-II™ Label Artist™ Web Label Artist™ Mobile (Android/iOS) mPrint App (Android/iOS) BarTender® Ultralite for BIXOLON
MDM (Optional)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android), SOTI® Connect supported
Fonts / Graphics / Symbologies	
Fonts	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E, 9 BPL-D), Scalable Fonts (1 SLCS, 1 BPL-Z, 1 BPL-D), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)
Downloadable Objects	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos
Barcode Symbologies	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39
Accessories / Supplies/ Warranty	
Included in the Box	AC/DC Adapter, Power Cord, USB Cable XD5-40t: Holder Ribbon x 2, Core Paper (0.5-inch, 1-inch)
Options & Accessories	Peeler, Auto Cutter, External Paper Supply, Serial Cable
Compatible Supplies	B-ribbon™, B-band™
Warranty	3 Years
RFID	
Frequency	UHF, 865 to 928 MHz
Transmit Power	1W
Modulation	ASK
Protocol	ISO 18000-63 (EPC Class1 Gen2V2)
Auto Cutter	Optional
Tag Pitch	Min 16 mm



XD5-40IId XD5-40IIt XD5-40IItR XD5-40IIt-H



XD7-20d XD7-20d-H

XD5-40II Series

XD7-20d

	XD5-40II Series	XD7-20d
Print Characteristics		
Print Method	XD5-40IId: Direct Thermal XD5-40IIt: Thermal Transfer or Direct Thermal	Direct Thermal
Print Speed	XD5-40IId: Up to 8 ips (203 mm/sec) XD5-43IId: Up to 6 ips (152 mm/sec) XD5-40IIt: Up to 8 ips (203 mm/sec) XD5-43IIt: Up to 6 ips (152 mm/sec)	XD7-20d: Up to 8 ips (203 mm/sec) XD7-23d: Up to 6 ips (152 mm/sec)
Print Resolution	XD5-40II: 203 dpi XD5-43II: 300 dpi	XD7-20d: 203 dpi XD7-23d: 300 dpi
Print Width	XD5-40II: Up to 108 mm XD5-43II: Up to 105.7 mm	XD7-20d: Up to 54 mm XD7-23d: Up to 56.9 mm
Print Length	Up to 1,000 mm	Up to 2,000 mm
Sensor	Transmissive (Fixed), Reflective (Adjustable), Head Open, Ribbon-End (XD5-40IIt / XD5-40IItR only)	Transmissive (Multi-position), Reflective (Adjustable), Head Open
Media Characteristics		
Media Type	Gap, Black Mark, Notch, Continuous, Fan-Fold	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	15 to 118 mm	15 to 60 mm
Media Roll Diameter	Up to 127 mm	Up to 127 mm
Media Thickness	0.06 to 0.20 mm	0.06 to 0.20 mm
Supply Method	Easy Paper Loading	Easy Paper Loading
Inner Core	25.4 to 38.1 mm	12.5 to 38.1 mm
Ribbon Characteristics		
Ribbon Type	Wax, Wax/Resin, Resin, Outside	-
Ribbon Width	33 to 110 mm	-
Ribbon Length	Up to 300 m	-
Core Inner Diameter	25.4 mm, 12.7 mm	-
Physical Characteristics		
Dimensions (W x L x H)	XD5-40IId: 194 x 248 x 169 mm (7.64 x 9.76 x 6.65 inch) XD5-40IIt: 210 x 284 x 188 mm (8.3 x 11.2 x 7.4 inch)	111 x 219 x 150 mm (4.37 x 8.62 x 5.9 inch) LCD Model: 111 x 219 x 160 mm (4.37 x 8.62 x 6.3 inch)
Weight	XD5-40IId: 2.01 kg (4.43 lbs.) XD5-40IIt: 2.48 kg (5.46 lbs.)	1.11 kg (2.45 lbs.) LCD Model: 1.25 kg (2.76 lbs.)
Electrical	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz
Display	XD5-40IId & XD5-40IIt Standard: None Optional: FSTN LCD (200 x 100 pixels) XD5-40IId-H, XD5-40IIt-H, XD5-40IItR Standard: FSTN LCD (200 x 100 pixels)	XD7-20d Standard: None Optional: 4.3-inch Colour Touch LCD XD7-20d-H Standard: 4.3-inch Colour Touch LCD
Performance Characteristics		
Memory	512 MB SDRAM, 512 MB Flash	512 MB SDRAM, 512 MB Flash Flash memory expandable up to 1GB
Interface	Standard: USB + USB Host Optional: ① USB + USB Host + Serial + Ethernet ② USB + USB Host + Serial + Ethernet + WLAN ③ USB + USB Host + Serial + Ethernet + Bluetooth® XD5-40IItR / XD5-40IId-H, XD5-40IIt-H Standard: USB + USB Host + Serial + Ethernet Optional: ① USB + USB Host + Serial + Ethernet + WLAN ② USB + USB Host + Serial + Ethernet + Bluetooth WLAN: 2.4G/5GHz, 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) Ethernet: 10/100Mbps	Standard: USB + USB Host Optional: ① USB + USB Host + Serial ② USB + USB Host + Ethernet ③ USB + USB Host + WLAN[1] ④ USB + USB Host + Bluetooth® ⑤ USB + USB Host + WLAN[2] and Bluetooth® Ethernet: 10/100Mbps WLAN[1]: 2.4G/5GHz, 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) WLAN[2]: 2.4G/5GHz, 802.11a/b/g/n/ac/ax (Infrastructure, Wi-Fi Direct, SoftAP)
Real Time Clock	Supported (Optional)	Supported
Environment Characteristics		
Temperature	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 5 to 95% RH	Operating: 10 to 80% RH Storage: 5 to 95% RH
Software		
Emulation	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ , DPL XML	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL), XML
Driver / Utility	Windows® Driver (Europlus/Seagull) Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program OPOS/JPOS Driver Device Driver for SAP® Network Auto Installer	Windows® Driver (Europlus/Seagull) Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program OPOS/JPOS Driver Device Driver for SAP® Network Auto Installer
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) XI (Optional) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) XI (Optional) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK
Design & Print	Label Artist-II™ Label Artist™ Web Label Artist™ Mobile (Android/iOS) mPrint App (Android/iOS) BarTender® Ultralite for BIXOLON	Label Artist-II™ Label Artist™ Web Label Artist™ Mobile (Android/iOS) mPrint App (Android/iOS) BarTender® Ultralite for BIXOLON
MDM (Optional)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/ Android), SOTI® Connect supported
Fonts / Graphics / Symbologies		
Fonts	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E, 9 BPL-D), Scalable Fonts (1 SLCS, 1 BPL-Z, 1 BPL-D), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E, 9 BPL-D), Scalable Fonts (1 SLCS, 1 BPL-Z, 1 BPL-D), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)
Downloadable Objects	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos
Barcode Symbologies	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39
Accessories / Supplies / Warranty		
Included in the Box	AC/DC Adapter, Power Cord, USB Cable XD5-40IIt, XD5-40IItR, XD5-40IIt-H: Holder Ribbon x 2, Core Paper (0.5-inch, 1-inch)	AC/DC Adapter, Power Cord, USB Cable
Options & Accessories	Peeler, Auto Cutter, External Paper Supply, Serial Cable	Peeler, Auto Cutter, Serial Cable, Touch LCD
Compatible Supplies	B-ribbon™, B-band™	-
Warranty	3 Years	3 Years
RFID		
Frequency	UHF, 865 to 928 MHz	-
Transmit Power	1W	-
Modulation	ASK	-
Protocol	ISO 18000-63 (EPC Class1 Gen2V2)	-
Auto Cutter	Optional	-
Tag Pitch	Min 16 mm	-





	XQ-840II	XL5-40
Print Characteristics		
Print Method	Direct Thermal	Direct Thermal
Print Speed	XQ-840II: Up to 6 ips (152 mm/sec) XQ-843II: Up to 5 ips (127 mm/sec)	XL5-40: Up to 6 ips (152 mm/sec) XL5-43: Up to 5 ips (127 mm/sec)
Print Resolution	XQ-840II: 203 dpi XQ-843II: 300 dpi	XL5-40: 203 dpi XL5-43: 300 dpi
Print Width	XQ-840II: Up to 108 mm XQ-843II: Up to 105.7 mm	XL5-40: Up to 108 mm XL5-43: Up to 105.7 mm
Print Length	Up to 1,000 mm	30 to 1,000 mm
Sensor	Transmissive, Reflective (Adjustable), Head Open	Gap (Fixed) / Black mark (Adjustable), Head Open, Paper Taken Sensor
Media Characteristics		
Media Type	Gap, Black Mark, Notch, Continuous, Fan-Fold	Linerless: Continuous, Black Mark Liner: Gap, Black Mark, Fan-Fold
Media Width	15 to 118 mm	20 to 114 mm
Media Roll Diameter	Up to 130 mm	Up to 127 mm
Media Thickness	0.06 to 0.20 mm	0.09 to 0.20 mm
Supply Method	Easy Paper Loading	-
Inner Core	25.4 to 38.1 mm (With Wall Mount Bracket: 25.4mm)	38.1 mm (1.5 inch) - Recommended, 25.4 mm (1 inch)
Ribbon Characteristics		
Ribbon Type	-	-
Ribbon Width	-	-
Ribbon Length	-	-
Core Inner Diameter	-	-
Physical Characteristics		
Dimensions (W x L x H)	194 x 273 x 214 mm (7.63 x 10.74 x 8.43 inch)	186 x 287.7 x 173 mm (7.32 x 11.33 x 6.81 inch)
Weight	2.42 kg (5.34 lbs.)	2.8 kg (6.17 lbs.)
Electrical	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz
Display	8-inch IPS TFT Touch LCD (800 x 1280 pixels) Android 13	Standard: None Optional: FSTN LCD (200 x 100 pixels)
Performance Characteristics		
Memory	Printer: 512 MB SDRAM, 512 MB Flash Tablet: 4 GB RAM, 64GB Flash	Standard: 64 MB SDRAM, 128 MB Flash Optional: 256 MB SDRAM, 256 MB Flash
Interface	USB + 2 USB Host + WLAN + Bluetooth® USB: For printer 2 USB Host, WLAN, Bluetooth : For tablet WLAN: 802.11a/b/g/n/ac (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP)	Standard: USB + USB Host Optional: ① USB + USB Host + WLAN ② USB + USB Host + Bluetooth ③ USB + USB Host + Serial + Ethernet ④ USB + USB Host + Serial + Ethernet + WLAN ⑤ USB + USB Host + Serial + Ethernet + Bluetooth® WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) Ethernet: 10/100Mbps
Real Time Clock	-	Supported (Optional)
Environment Characteristics		
Temperature	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 5 to 95% RH	Operating: 10 to 80% RH Storage: 5 to 95% RH
Software		
Emulation	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BXL/POS™, XML	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL, Optional), XML(Optional)
Driver / Utility	Windows® Driver (Europlus/Seagull) BIXOLON Utility	Windows® Driver (Europlus/Seagull) Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program OPOS/JPOS Driver Device Driver for SAP® Network Auto Installer
Developer Tools	Android™/Windows SDK Web Print SDK (Android/iOS/Windows/macOS) Xamarin® SDK MAUI(Multi-Platform App UI) SDK React Native® SDK Cordova™ Plugin Flutter™ Plugin	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) XI(Optional) Cordova™ Plugin Flutter™ Plugin React Native® SDK
Design & Print	Label Artist™ Mobile Label Artist™ Web Food Labelling App mPrint App	Label Artist-II™ Label Artist™ Web Label Artist™ Mobile (Android/iOS) mPrint App (Android/iOS) BarTender® Ultralite for BIXOLON
MDM (Optional)	BIXOLON Profile Manager - XCM™ (Android)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android), SOTI® Connect supported
Fonts / Graphics / Symbologies		
Fonts	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E), Scalable Fonts (1 SLCS, 1 BPL-Z), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E), Scalable Fonts (1 SLCS, 1 BPL-Z), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)
Downloadable Objects	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos
Barcode Symbologies	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39
Accessories / Supplies / Warranty		
Included in the Box	AC/DC Adapter, Power Cord, USB Cable	AC/DC Adapter, Power Cord, USB Cable
Options & Accessories	Peeler, Auto Cutter, Wall Mount	Serial Cable
Compatible Supplies	-	B-linerless™
Warranty	2 Years	2 Years





XT5-40



XT5-40NR

	XT3-40	XT5-40 Series
Print Characteristics		
Print Method	Thermal Transfer or Direct Thermal	Thermal Transfer or Direct Thermal
Print Speed	XT3-40: Up to 8 ips (203 mm/sec) XT3-43: Up to 6 ips (152 mm/sec)	XT5-40: Up to 14 ips (356 mm/sec) XT5-43: Up to 10 ips (254 mm/sec) XT5-46: Up to 5 ips (127 mm/sec)
Print Resolution	XT3-40: 203 dpi XT3-43: 300 dpi	XT5-40: 203 dpi XT5-43: 300 dpi XT5-46: 600 dpi
Print Width	XT3-40: 108 mm XT3-43: 105.7 mm	XT5-40: 104 mm XT5-43: 105.7mm XT5-46: 105.6 mm
Print Length	XT3-40: Up to 4,000 mm XT3-43: Up to 2,000 mm	XT5-40: Up to 4,000 mm XT5-43: Up to 2,500 mm XT5-46: Up to 1,000 mm
Sensor	Transmissive (Adjustable), Reflective (Adjustable), Ribbon-End, Head Open	Transmissive (Adjustable), Reflective (Adjustable), Ribbon-End, Head Open
Media Characteristics		
Media Type	Gap, Black Mark, Notch, Continuous, Fan-Fold	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	20 to 114 mm	25 to 114 mm
Media Roll Diameter	Up to 203 mm	Up to 203 mm
Media Thickness	0.06 to 0.25 mm	0.06 to 0.30 mm
Supply Method	Easy Paper Loading	Easy Paper Loading
Inner Core	25.4 to 76.2 mm	38.1 to 76.2 mm, 25.4 mm (Optional)
Ribbon Characteristics		
Ribbon Type	Wax, Wax/Resin, Resin, Outside, Inside	Wax, Wax/Resin, Resin, Outside, Inside
Ribbon Width	40 to 110 mm	50 to 110 mm
Ribbon Length	Up to 450 m	Up to 450 m
Core Inner Diameter	25.4 mm	25.4 mm
Physical Characteristics		
Dimensions (W x L x H)	Standard: 240 x 430.5 x 276.7 mm 9.44 x 16.94 x 10.89 inch) External Rewinder: 240 x 430.5 x 326.7 mm(9.44 x 16.94 x 12.86 inch)	Standard: 269 x 490 x 324 mm 10.59 x 19.29 x 12.76 inch) External Rewinder: 269 x 490 x 407 mm(10.59 x 19.29 x 16.02 inch)
Weight	Standard: 9.3 kg (20.5 lbs.) External Rewinder: 11.88 kg (26.19 lbs.)	Standard: 13.98 kg (30.82 lbs.) External Rewinder: 17.98 kg (39.64 lbs.)
Electrical	EnergyStar® Certified, Internal Power Adapter 100-240 VAC, 50-60 Hz	Internal Power Adapter 100-120 V/200-240 VAC, 50/60 Hz
Display	2.4-inch Colours TFT LCD	XT5-40: 3.5-inch HVGA (262K Colours) TFT LCD XT5-40N: 4.3-inch CTP Touch TFT LCD
Performance Characteristics		
Memory	128 MB SDRAM, 128 MB Flash	512 MB SDRAM, 512 MB Flash
Interface	Standard: USB + USB Host + Serial + Ethernet Optional: ① USB + USB Host + Serial + Ethernet + Parallel ② USB + USB Host + Serial + Ethernet + Parallel + Bluetooth® ③ USB + USB Host + Serial + Ethernet + Parallel + WLAN ④ USB + USB Host + Serial + Ethernet + Bluetooth ⑤ USB + USB Host + Serial + Ethernet + WLAN Ethernet: 10/100 Mbp WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) * WLAN & Bluetooth: Dongle type not supported	Standard: USB + Serial + Ethernet + 2 USB Host ports Optional: ① USB + Serial + Parallel or GPIO + Ethernet + 2 USB Host ports ② USB + WLAN + Ethernet + 2 USB Host ports ③ USB + WLAN + Parallel + Ethernet + 2 USB Host ports ④ USB + Bluetooth® + Ethernet + 2 USB Host ports ⑤ USB + Bluetooth + Parallel + Ethernet + 2 USB Host ports Ethernet: 10/100/1000 Mbps (1Gbps) WLAN: 2.4G/5GHz, 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) GPIO: DB15 (Female), 5/24 V, 4 GPI, 8 GPO
Real Time Clock	Supported	Supported
Environment Characteristics		
Temperature	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 5 to 95% RH	Operating: 10 to 80% RH Storage: 5 to 95% RH
Software		
Emulation	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL), XML	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL), XML
Driver / Utility	Windows® Driver (Europlus/Seagull) Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program OPOS/JPOS Driver Device Driver for SAP® Network Auto Installer	Windows® Driver (Europlus/Seagull) Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program OPOS/JPOS Driver Device Driver for SAP® Network Auto Installer
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) XI(Optional) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) XI(Optional) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK
Design & Print	Label Artist-II™ Label Artist™ Web Label Artist™ Mobile (Android/iOS) mPrint App (Android/iOS) BarTender® Ultralite for BIXOLON	Label Artist-II™ Label Artist™ Web Label Artist™ Mobile (Android/iOS) mPrint App (Android/iOS) BarTender® Ultralite for BIXOLON
MDM (Optional)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android), SOTI® Connect supported
Fonts / Graphics / Symbologies		
Fonts	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E), Scalable Fonts (1 SLCS, 1 BPL-Z), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E, 9 BPL-D), Scalable Fonts (1 SLCS, 1 BPL-Z, 1 BPL-D), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)
Downloadable Objects	Supporting user-defined fonts (TTF,TTE,FNT), graphics, formats and logos	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos
Barcode Symbologies	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39
Accessories / Supplies / Warranty		
Included in the Box	Power Cord, USB Cable	Power Cord
Options & Accessories	Peeler, Auto Cutter, External Rewinder (Max.O.D. 130 mm), Serial Cable, Parallel Cable	Peeler, Auto Cutter, External Rewinder (Max.O.D. 203 mm), 1-inch I.D. Core Media Supply Hanger Serial Cable, Parallel Cable, USB Cable
Compatible Supplies	B-ribbon™	B-ribbon™
Warranty	2 Years	2 Years
RFID		
Frequency	-	UHF, 865 to 928 MHz
Transmit Power	-	1W
Modulation	-	ASK
Protocol	-	ISO 18000-63 (EPC Class1 Gen2V2)
Auto Cutter	-	Optional
Tag Pitch	-	Min 16 mm





	STP-103III	SRP-330III
Print Characteristics		
Print Method	Direct Thermal	Direct Thermal
Print Speed	Up to 80 mm/sec	Up to 250 mm/sec
Print Resolution	203 dpi	SRP-330III: 180 dpi SRP-332III: 203 dpi
Print Width	Up to 48 mm	Up to 72 mm
Sensor	Paper End, Paper Near End, Cover Open	Paper End, Cover Open
Media Characteristics		
Media Type	Receipt	Receipt
Media Width	57.5 mm	80 mm Optional 58 mm using 2-inch Partition
Media Roll Diameter	Up to 60 mm	Up to 83 mm
Media Thickness	0.05 to 0.08 mm	0.05 to 0.08 mm
Supply Method	Easy Paper Loading	Easy Paper Loading
Physical Characteristics		
Dimensions (W x L x H)	116 x 180 x 90 mm (4.56 x 7.08 x 3.54 inch)	145 x 195 x 146 mm (5.72 x 7.79 x 5.74 inch)
Weight	450 g (0.99 lbs.)	1.6 kg (3.52 lbs.)
Electrical	External Power Adapter 100-240 VAC, 50/60Hz	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz
Drawer Port	2 ports (Via Y-Type Adapter)	2 ports (Via Y-Type Adapter)
Performance Characteristics		
Memory	-	128 Mb SDRAM, 64 Mb Flash
NV Image Memory	256 Kbytes (Mono)	768 Kbytes (Mono)
Receive Buffer	64 Kbytes	4 Kbytes
User Define Buffer	12 Kbytes	12 Kbytes
Interface	① USB 2.0 FS + Serial ② USB 2.0 FS + Parallel	① USB 2.0 FS + Ethernet + Serial ② USB 2.0 FS + Serial ③ USB 2.0 FS + Parallel ④ USB 2.0 FS + Dual Serial (Korea only)
Environment Characteristics		
Temperature	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 10 to 90% RH	Operating: 10 to 80% RH Storage: 10 to 90% RH
Software		
Emulation	BXL/POS™	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program Network Auto Installer
Driver / Utility	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK
Developer Tools	Android™ SDK Linux SDK Web Print SDK (Android)	mPrint App (Android/iOS) POS Artist™ (Windows)
Design & Print	-	mPrint App (Android, iOS)
MDM (Optional)	-	-
Fonts / Graphics / Symbologies		
Character Size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24
Characters per Line	Font A: 32, Font C: 42, KOR, CHN, JPN: 16	SRP-330III: Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21 SRP-332III: Font A: 48, Font B, C: 64, KOR, CHN, JPN: 24
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 33 page International: 32	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32
Barcode Symbologies	-	1D: Coda Bar, Code39, Code93, Code128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, PDF417, QR Code
Accessories / Supplies / Warranty		
Included in the Box	Paper, USB A-B Cable 1.8 m, Power cord, AC Adapter, Serial Cable (25-9 pin), Parallel Cable	Paper, Cable Cover, AC/DC Adapter, Power Cord, 2-inch Partition (58 mm), USB A-B Cable 1.8 m
Options & Accessories	External Buzzer, B-Melodist	External Buzzer, B-Melodist, Serial Cable (9-9/25-9 pin), Parallel Cable
Warranty	2 Years	2 Years





	SRP-350V	SRP-350plusV
Print Characteristics		
Print Method	Direct Thermal	Direct Thermal
Print Speed	SRP-350V: Up to 300 mm/sec SRP-352V: Up to 270 mm/sec	SRP-350plusV: Up to 400 mm/sec SRP-352plusV: Up to 370 mm/sec
Print Resolution	SRP-350V: 180 dpi SRP-352V: 203 dpi	SRP-350plusV: 180 dpi SRP-352plusV: 203 dpi
Print Width	Up to 72 mm	Up to 72 mm
Sensor	Paper End, Paper Near End, Cover Open, Visibility Intelligence Sensor	Paper End, Paper Near End, Cover Open, Visibility Intelligence Sensor
Media Characteristics		
Media Type	Receipt	Receipt
Media Width	80 mm Optional 58 mm using 2-inch Partition	80 mm Optional 58 mm using 2-inch Partition
Media Roll Diameter	Up to 83 mm	Up to 83 mm
Media Thickness	0.05 to 0.08 mm	0.05 to 0.08 mm
Supply Method	Easy Paper Loading	Easy Paper Loading
Physical Characteristics		
Dimensions (W x L x H)	145 x 204 x 146 mm (5.7 x 8.03 x 5.74 inch)	145 x 200 x 146 mm (5.70 x 7.87 x 5.74 inch)
Weight	1.6 kg (3.52 lbs.)	1.6 kg (3.52 lbs.)
Electrical	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz
Drawer Port	2 ports (Via Y-Type Adapter)	2 ports (Via Y-Type Adapter)
Performance Characteristics		
Memory	64 Mb SDRAM, 64 Mb Flash	64 Mb SDRAM, 64 Mb Flash
NV Image Memory	256 Kbytes (Mono)	768 Kbytes (Mono)
Receive Buffer	4 Kbytes	4 Kbytes
User Define Buffer	12 Kbytes	12 Kbytes
Interface	Standard: USB 2.0 FS Optional: ① USB 2.0 FS + Serial ② USB 2.0 FS + Parallel ③ USB 2.0 FS + Ethernet ④ USB 2.0 FS + Dual Serial (Korea only)	Standard: USB 2.0 FS + Ethernet Optional: ① USB 2.0 FS + Ethernet + Serial ② USB 2.0 FS + Ethernet + Dual Serial ③ USB 2.0 FS + Ethernet + Parallel ④ USB 2.0 FS + Ethernet + WLAN[1] ⑤ USB 2.0 FS + Ethernet + Bluetooth® ⑥ USB 2.0 FS + Ethernet +Powered USB WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP)
Environment Characteristics		
Temperature	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 10 to 90% RH	Operating: 10 to 80% RH Storage: 10 to 90% RH
Software		
Emulation	BXL/POS™	Windows® Driver OPOS/JPOS Driver Linux/Mac® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program Network Auto Installer
Driver / Utility	Windows® Driver OPOS/JPOS Driver Linux/Mac® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program Network Auto Installer	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK B-gate SDK_Cloud Server Print, B-gate SDK_Web App Print
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK B-gate SDK_Cloud Server Print, B-gate SDK_Web App Print	mPrint App (Android/iOS) POS Artist™ (Windows)
Design & Print	mPrint App (Android/iOS) POS Artist™ (Windows)	BIXOLON Profile Manager - XPM™, XCM™ (Windows, Android)
MDM (Optional)	-	BIXOLON Profile Manager - XPM™, XCM™ (Windows, Android)
Fonts / Graphics / Symbologies		
Character Size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24
Characters per Line	SRP-350V: Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21 SRP-352V: Font A: 48, Font B, C: 64, KOR, CHN, JPN: 24	SRP-350plusV: Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21 SRP-352plusV: Font A: 48 Font B, C: 64 KOR, CHN, JPN: 24
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32
Barcode Symbologies	1D: Coda Bar, Code39, Code93, Code128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, PDF417, QR Code	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, PDF417, QR code
Accessories / Supplies / Warranty		
Included in the Box	Paper, AC/DC Adapter, Cable Cover, Power Cord, USB A-B Cable 1.8 m	Paper, AC/DC Adapter, Cable Cover, Power Cord, USB A-B Cable 1.8 m, DK Gender
Options & Accessories	Bulit-in AC/DC Adapter, Vertical Stand, Wall Mount, Splash Proof Cover, External Buzzer, B-Melodist, Serial Cable (9-9/25-9 pin), Parallel Cable, 2-inch Partition (58 mm)	Bulit-in AC/DC Adapter, Vertical Stand, Wall Mount, Splash Proof Cover, External Buzzer, B-Melodist, Powered USB (0.5/1.2 m), Serial Cable (9-9/25-9 pin), Powered A-B USB Y Cable (1.2/4.8 m), Parallel Cable, 2-inch Partition (58 mm)
Warranty	2 Years	2 Years







	SRP-380	SRP-380plus	SRP-F310II
Print Characteristics			
Print Method	Direct Thermal	Direct Thermal	Direct Thermal (Front Exit)
Print Speed	Up to 350 mm/sec	Up to 500 mm/sec	Up to 350 mm/sec
Print Resolution	SRP-380: 180 dpi SRP-382: 203 dpi	SRP-380plus: 180 dpi SRP-382plus: 203 dpi	SRP-F310II: 180 dpi (512 dots) SRP-F312II: 203 dpi (576 dots) SRP-F313II: 203 dpi (640 dots)
Print Width	Up to 72 mm	Up to 72 mm	SRP-F310II: Up to 72 mm SRP-F312II: Up to 72 mm SRP-F313II: Up to 80 mm
Sensor	Paper End, Paper Near End, Cover Open, Visibility Intelligence Sensor	Paper End, Paper Near End, Cover Open, Visibility Intelligence Sensor	Paper End, Paper Near End, Cover Open
Media Characteristics			
Media Type	Receipt	Receipt	Receipt
Media Width	80 mm Optional 58 mm using 2-inch Partition	80 mm Optional 58 mm using 2-inch Partition	Standard 80 mm, Optional 83 mm by removing 3-inch Partition
Media Roll Diameter	Up to 83 mm	Up to 83 mm	Up to 105 mm
Media Thickness	0.05 to 0.08 mm	0.05 to 0.08 mm	0.05 to 0.08 mm
Supply Method	Easy Paper Loading	Easy Paper Loading	Easy Paper Loading
Physical Characteristics			
Dimensions (W x L x H)	147 x 200 x 148 mm (5.79 x 7.87 x 5.82 inch)	147 x 200 x 148 mm (5.79 x 7.87 x 5.82 inch)	154 x 203 x 148 mm (6.06 x 7.99 x 5.82 inch)
Weight	1.56 kg (3.43 lbs.)	1.57 kg (3.46 lbs.)	2.00 kg (4.40 lbs.)
Electrical	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz	EnergyStar® Certified, External Power Supply Housed Internally (Adapter 24 V/2.5 A, 50/60 Hz)
Drawer Port	2 ports (Via Y-Type Adapter)	2 ports (Via Y-Type Adapter)	2 ports (Via Y-Type Adapter)
Performance Characteristics			
Memory	128 Mb SDRAM, 64 Mb Flash	128 Mb SDRAM, 64 Mb Flash	-
NV Image Memory	768 Kbytes (Mono)	768 Kbytes (Mono)	768 Kbytes (Mono)
Receive Buffer	4 Kbytes	4 Kbytes	4 Kbytes
User Define Buffer	12 Kbytes	12 Kbytes	12 Kbytes
Interface	Standard: USB 2.0 FS Optional: ① USB 2.0 FS + Ethernet ② USB 2.0 FS +Serial ③ USB 2.0 FS + Dual Serial ④ USB 2.0 FS + WLAN ⑤ USB 2.0 FS + Bluetooth® ⑥ USB 2.0 FS + Powered USB WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP)	Standard: USB 2.0 FS + Ethernet Optional: ① USB 2.0 FS + Ethernet + Serial ② USB 2.0 FS + Ethernet + Dual Serial ③ USB 2.0 FS + Ethernet + Parallel ④ USB 2.0 FS + Ethernet + WLAN ⑤ USB 2.0 FS + Ethernet + Bluetooth® ⑥ USB 2.0 FS + Ethernet +Powered USB WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP)	Standard: USB 2.0 FS + Ethernet Optional: ① USB 2.0 FS + Ethernet + Serial ② USB 2.0 FS + Ethernet + Dual Serial ③ USB 2.0 FS + Ethernet + Parallel ④ USB 2.0 FS + Ethernet + WLAN[1] ⑤ USB 2.0 FS + Ethernet + Bluetooth® SRP-F310IIHi (B-gate Hub Interface): 3 USB Type-A (Host, 2.0 HS) + 1 USB Type-B (2.0 HS) + 1 USB Type-A (Charging only) + Ethernet + WLAN[2] WLAN[1]: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) WLAN[2]: 802.11a/ac/b/g/n USB dongle type (Optional)
Environment Characteristics			
Temperature	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 10 to 90% RH	Operating: 10 to 80% RH Storage: 10 to 90% RH	Operating: 10 to 80% RH Storage: 10 to 90% RH
Sealing	-	-	IP12
Software			
Emulation	BXL/POS™	BXL/POS™	BXL/POS™
Driver / Utility	Windows® Driver OPOS/JPOS Driver Linux/Mac® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program Network Auto Installer	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program Network Auto Installer	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program Network Auto Installer SRP-F310IIHi: Utility Program
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Windows Runtime SDK Xamarin® SDK Web Print SDK Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK B-gate SDK_Cloud Server Print, B-gate SDK_Web App Print	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK B-gate SDK_Cloud Server Print, B-gate SDK_Web App Print	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin SRP-F310IIHi: B-gate iOS/Android/Windows SDK Chrome SDK, B-gate SDK_Cloud Server Print, B-gate SDK_Web App Print MAUI SDK Flutter™ Plugin React Native® SDK
Design & Print	mPrint App (Android/iOS) POS Artist™ (Windows)	mPrint App (Android/iOS) POS Artist™ (Windows)	mPrint App (Android/iOS) POS Artist™ (Windows)
MDM (Optional)	BIXOLON Profile Manager - XPM™, XCM™ (Windows, Android)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android)
Fonts / Graphics / Symbologies			
Character Size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24
Characters per Line	SRP-380: Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21 SRP-382: Font A: 48, Font B, C: 64, KOR, CHN, JPN: 24	SRP-380plus: Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21 SRP-382plus: Font A: 48 Font B, C: 64, KOR, CHN, JPN: 24	SRP-F310II: Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21 SRP-F312II: Font A: 48, Font B, C: 64, KOR, CHN, JPN: 24 SRP-F313II: Font A: 53, Font B, C: 71, KOR, CHN, JPN: 26
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32 Unicode: UTF-8, UTF-16, UTF-32	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32
Barcode Symbologies	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, GS1-128, GS1 DataBar Stacked/Omnidirectional/Truncated/Limited/ Expanded, PDF417, QR code	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, GS1-128, GS1 DataBar Stacked/Omnidirectional/Truncated/ Limited/Expanded, PDF417, QR code	1D: Coda Bar, Code39, Code93, Code128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, PDF417, QR Code
Accessories / Supplies / Warranty			
Included in the Box	Paper, AC/DC Adapter, Power Cord, Cable Cover, 2-inch Partition (58 mm), USB A-B Cable 1.8 m	Paper, AC/DC Adapter, Cable Cover, Power Cord, 2-inch Partition (58 mm), USB A-B Cable 1.8 m, DK Gender	Paper, AC/DC Adapter, Power Cord, USB A-A Cable 1.8 m, 3-inch Partition (83 mm)
Options & Accessories	Splash Proof Cover, External Buzzer, B-Melodis, Powered USB (0.5/1.2 m), Powered A-B USB Y Cable (1.2/4.8 m), Serial Cable (9-9/25-9 pin)	Bulit-in AC/DC Adapter Vertical Stand, Wall Mount, Splash Proof Cover, External Buzzer, B-Melodist, Powered USB (0.5/1.2 m), Powered A-B USB Y Cable (1.2/4.8 m), Serial Cable (9-9/25-9 pin),	External Buzzer B-Melodist Serial Cable (9-9/25-9 pin), Parallel Cable
Warranty	2 Years	2 Years	2 Years





	SRP-Q200	SRP-QE300
Print Characteristics		
Print Method	Direct Thermal	Direct Thermal
Print Speed	Up to 250 mm/sec	Up to 200 mm/sec
Print Resolution	203 dpi	SRP-QE300: 180 dpi SRP-QE302: 203 dpi
Print Width	Up to 54 mm	Up to 72 mm
Sensor	Paper End, Cover Open	Paper End, Cover Open
Media Characteristics		
Media Type	Receipt	Receipt
Media Width	58 mm	80 mm Optional 58 mm using 2-inch Partition
Media Roll Diameter	Up to 60 mm	Up to 80 mm
Media Thickness	0.05 to 0.08 mm	0.05 to 0.08 mm
Supply Method	Easy Paper Loading	Easy Paper Loading
Physical Characteristics		
Dimensions (W x L x H)	103 x 104 x 109 mm (4.03 x 4.10 x 4.24 inch)	128 x 125 x 125 mm (5.03 x 4.92 x 4.92 inch)
Weight	0.61 kg (1.34 lbs.)	1.13 kg (2.49 lbs.)
Electrical	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz
Drawer Port	2 ports (Via Y-Type Adapter)	2 ports (Via Y-Type Adapter)
Performance Characteristics		
Memory	-	-
NV Image Memory	768 Kbytes (mono)	768 Kbytes (Mono)
Receive Buffer	4 Kbytes	4 Kbytes
User Define Buffer	12 Kbytes	12 Kbytes
Interface	Standard: ① USB 2.0 FS + Serial ② USB 2.0 FS + Ethernet Optional: ① USB 2.0 FS + Ethernet + WLAN ② USB 2.0 FS + Ethernet + Bluetooth® WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP)	USB 2.0 FS + Ethernet
Environment Characteristics		
Temperature	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 10 to 90% RH	Operating: 10 to 80% RH Storage: 10 to 90% RH
Software		
Emulation	BXL/POS™	BXL/POS™
Driver / Utility	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK
Design & Print	mPrint App (Android/iOS) POS Artist™ (Windows)	mPrint App (Android/iOS) POS Artist™ (Windows)
MDM (Optional)	-	-
Fonts/Graphics/Symbologies		
Character Size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24
Characters per Line	Font A: 36, Font B, C: 48, KOR, CHN, JPN: 18	SRP-QE300: Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21 SRP-QE302: Font A: 48, Font B, C: 64, KOR, CHN, JPN: 24
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32
Barcode Symbologies	1D: Coda Bar, Code39, Code93, Code128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, PDF417, QR Code	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, GS1-128, GS1 DataBar Stacked/ Omnidirectional/ Truncated/ Limited/ Expanded, PDF417, QR code
Accessories / Supplies / Warranty		
Included in the Box	Paper, AC/DC Adapter, Power Cord, USB A-B Cable 1.8 m	Paper, AC/DC Adapter, Power Cord, USB A-B Cable 1.8 m
Options & Accessories	External Buzzer, B-Melodist, Serial Cable (9-9 pin)	Tablet Stand, External Buzzer, B-Melodist, 2-inch Partition (58 mm)
Warranty	2 Years	2 Years



SRP-Q300



SRP-Q300B



	SRP-Q300 Series	SRP-Q300II
Print Characteristics		
Print Method	Direct Thermal	Direct Thermal
Print Speed	Up to 220 mm/sec	Up to 250 mm/sec
Print Resolution	SRP-Q300: 180 dpi SRP-Q302: 203 dpi	203 dpi
Print Width	Up to 72 mm	Up to 72 mm
Sensor	Paper End, Cover Open	Paper End, Cover Open, Near End
Media Characteristics		
Media Type	Receipt	Receipt
Media Width	80 mm Optional 58 mm using 2-inch Partition	80 mm Optional 58 mm using 2-inch Partition
Media Roll Diameter	Up to 80 mm	Up to 81 mm
Media Thickness	0.05 to 0.08 mm	0.05 to 0.08 mm
Supply Method	Easy Paper Loading	Easy Paper Loading
Physical Characteristics		
Dimensions (W x L x H)	SRP-Q300 128 x 125 x 125 mm (5.03 x 4.92 x 4.92 inch) SRP-Q300B 128 x 125 x 169.2 mm (5.03 x 4.92 x 6.66 inch)	128 x 125 x 125 mm (5.03 x 4.92 x 4.92 inch)
Weight	SRP-Q300: 1.23 kg (2.71 lbs.) SRP-Q300B: 1.72 kg (3.79 lbs.)	1.23 kg (2.71 lbs.)
Electrical	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz, 24 V Li-ion, 2850 mAh (Nominal), Rechargeable Charging time: Up to 4.0 hrs (SRP-Q300B Only)	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz
Drawer Port	2 ports (Via Y-Type Adapter)	2 ports (Via Y-Type Adapter)
Performance Characteristics		
Memory	-	-
NV Image Memory	768 Kbytes (Mono)	3 Mbytes (Mono)
Receive Buffer	4 Kbytes	-
User Define Buffer	12 Kbytes	12 Kbytes
Interface	Standard: USB Type-B (2.0 FS) + Ethernet + USB Type-A (Charging only) Optional: ① Standard + WLAN ② Standard + Bluetooth® WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP)	Standard: 3 USB Type-A (Host) + 1 USB Type-B + 1 USB Type-C® + Ethernet Optional: ① Standard + WLAN ② Standard + Bluetooth® USB: 2.0 HS (Type-C supports power delivery charging for mobile devices: Source, Delivers up to 18 W) WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP)
Environment Characteristics		
Temperature	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 10 to 90% RH	Operating: 10 to 80% RH Storage: 10 to 90% RH
Sealing	-	IP21
Software		
Emulation	BXL/POS™	BXL/POS™
Driver / Utility	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program Network Auto Installer SRP-Q300H: Utility Program	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program Network Auto Installer
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK B-gate SDK_Cloud Server Print, B-gate SDK_Web App Print
Design & Print	mPrint App (Android/iOS) POS Artist™ (Windows)	mPrint App (Android/iOS), POS Artist™ (Windows)
MDM (Optional)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android)
Fonts/Graphics/Symbologies		
Character Size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24
Characters per Line	SRP-Q300, Q300B: Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21 SRP-Q302, Q302B: Font A: 48, Font B, C: 64, KOR, CHN, JPN: 24	Font A: 48, Font B, C: 64, KOR, CHN, JPN: 24
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32 Unicode: UTF-8, UTF-16, UTF-32	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32
Barcode Symbologies	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, GS1-128, GS1 DataBar Stacked/ Omnidirectional/ Truncated/ Limited/ Expanded, PDF417, QR code	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, GS1-128, GS1 DataBar Stacked/ Omnidirectional/ Truncated/ Limited/ Expanded, PDF417, QR code
Accessories / Supplies / Warranty		
Included in the Box	Paper, AC/DC Adapter, Power Cord, Foot Rubber, USB A-B Cable 1.8 m	Paper, AC/DC Adapter, Foot Rubber, Power Cord, EMI Core
Options & Accessories	Tablet Stand, Mini LCD Display, External Buzzer, B-Melodist, 2-inch Partition (58 mm)	USB A-B Cable 1.8 m, USB C-C Cable 1 m, Tablet Stand, Mini LCD Display External Buzzer, B-Melodist, 2-inch Partition (58 mm)
Warranty	2 Years	2 Years





SRP-S300



SRP-S320

	SRP-S200	SRP-S300 Series
Print Characteristics		
Print Method	Direct Thermal	Direct Thermal
Print Speed	Up to 150 mm/sec	SRP-S300L,LX: Up to 170 mm/sec SRP-S300R: Up to 300 mm/sec SRP-S320: Up to 150 mm/sec
Print Resolution	203 dpi	203 dpi
Print Width	Up to 54/32 mm	SRP-S300: Up to 32/48/60/72/80 mm SRP-S320: Up to 32/48/60/72 mm
Sensor	Paper End, Black Mark, Cover Open, Paper Taken	SRP-S300: Paper End, Black Mark, Cover Open, Paper Taken (Option), Paper Near End (Receipt Only) SRP-S320: Paper End, Black Mark, Cover Open, Paper Taken
Media Characteristics		
Media Type	Linerless Restick	SRP-S300L,T: Linerless Restick SRP-S300LX,TX,SRP-S320: Linerless Permanent SRP-S300R: Receipt
Media Width	58 mm Optional 40 mm using Partition	Standard: 80 mm SRP-S300: Optional 40/58/62 using 2-inch Partition, 83 mm by removing 3-inch Partition SRP-S320: Optional 40/58/62 mm using 2-inch Partition
Media Roll Diameter	Up to 103 mm	SRP-S300: Up to 103 mm SRP-S320: Up to 120 mm
Media Thickness	0.06 to 0.09 mm	0.06 to 0.09 mm
Supply Method	Easy Paper Loading	Easy Paper Loading
Physical Characteristics		
Dimensions (W x L x H)	128 x 156 x 196 mm (5.03 x 6.14 x 7.71 inch)	SRP-S300: 156 x 210 x 160 mm (6.14 x 8.27 x 6.30 inch) SRP-S320: 156 x 227 x 161 mm (6.14 x 8.94 x 6.34 inch)
Weight	1.80 kg (3.96 lbs.)	SRP-S300: 2.00 kg (4.40 lbs.) SRP-S320: 2.20 kg (4.85 lbs.)
Electrical	EnergyStar® Certified, External Power Supply Housed Internally (Adapter 24 V/2.5 A)	EnergyStar® Certified, External Power Supply Housed Internally (Adapter 24 V/2.5 A)
Drawer Port	-	SRP-S300: 2 Ports (Via Y-Type Adapter) SRP-S320: N/A
Performance Characteristics		
Memory	-	16 MB RAM, 8 MB ROM
NV Image Memory	768 Kbytes (Mono)	SRP-S300: 256 Kbytes (Mono) SRP-S320: 768 Kbytes (Mono)
Receive Buffer	4 Kbytes	4 Kbytes
User Define Buffer	12 Kbytes	12 Kbytes
Interface	USB 2.0 FS + Ethernet + Serial	SRP-S300 Standard: USB 2.0 FS Optional: ① USB 2.0 FS + Serial ② USB 2.0 FS + Parallel ③ USB 2.0 FS + Ethernet ④ USB 2.0 FS + WLAN[1] ⑤ USB 2.0 FS + Bluetooth® SRP-S320 Standard: USB 2.0 FS + Ethernet Optional: ① USB 2.0 FS + Ethernet + Serial ② USB 2.0 FS + Ethernet + WLAN[1] ③ USB 2.0 FS + Ethernet + Bluetooth SRP-S300Hi, 320Hi (B-gate Hub Interface): 3 USB Type-A (Host, 2.0 HS) + 1 USB Type-A (Charging only) + 1 USB Type-B (2.0 HS) + Ethernet + WLAN[2] WLAN[1]: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) WLAN[2]: 802.11a/b/g/n/ac USB dongle type (Optional)
Environment Characteristics		
Temperature	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 10 to 90% RH	Operating: 10 to 80% RH Storage: 10 to 90% RH
Sealing	IP23	IP21
Software		
Emulation	BXL/POS™	BXL/POS™
Driver / Utility	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB/ Ethernet Driver Utility Program Network Auto Installer	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program Network Auto Installer SRP-S300,320Hi: Utility Program
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/ iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin SRP-S300,320Hi: B-gate iOS/Android/Windows SDK Chrome SDK, B-gate SDK_Cloud Server Print, B-gate SDK_Web App Print MAUI SDK Flutter™ Plugin React Native® SDK
Design & Print	mPrint App (Android/iOS) POS Artist™ (Windows)	mPrint App (Android/iOS) POS Artist™ (Windows)
MDM (Optional)	-	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android)
Fonts / Graphics / Symbologies		
Character Size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24
Characters per Line	Font A: 36, Font B, C: 48, KOR, CHN, JPN: 18	SRP-S300: Font A: 48, Font B, C: 64, SRP-S320: Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32	Alphanumeric: 95 Extended Graphics: 128 x 33 page International: 32
Barcode Symbologies	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, PDF417, QR code	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, PDF417, QR code
Accessories / Supplies / Warranty		
Included in the Box	Power Cord, 40 mm Partition, USB A-B Cable 1.8 m	Power Cord, USB A-B Cable 1.8 m, SRP-S300: 2-inch Partition (40/58/62 mm), 3-inch Partition (83 mm), SRP-S320: 2-inch Partition (40/58/62 mm)
Options & Accessories	External Buzzer, B-Melodist, USB to Serial Cable, Serial Cable (9-9 pin)	Wall Mount (SRP-S300 only), External Buzzer B-Melodist (SRP-S300 only), Serial Cable (9-9/25-9 pin),
Compatible Supplies	B-linerless™	B-linerless™
Warranty	2 Years	2 Years





	SRP-S300II	SRP-S3000
Print Characteristics		
Print Method	Direct Thermal	Direct Thermal
Print Speed	Up to 180 mm/sec	Up to 200 mm/sec
Print Resolution	203 dpi	203 dpi
Print Width	Up to 32/48/72 mm	Up to 32/48/72 mm
Sensor	Paper End, Black Mark, Cover Open, Paper Taken	Paper End, Black Mark, Cover Open, Paper Taken, Gap
Media Characteristics		
Media Type	Linerless Permanent, Linerless Restick, Receipt	Linerless Permanent, Linerless Restick, Liner Label (Gap, Black Mark, Notch, Continuous)
Media Width	80 mm Optional 40/58 mm	80 mm Optional 40/58 mm using 2-inch Partition
Media Roll Diameter	Up to 103 mm	Up to 103 mm
Media Thickness	0.06 to 0.09 mm	BXL/POS™-0.06 to 0.09 mm, SLCS™/BPL-Z™ (ZPL II®)/ BPL-C™ (CPCL)-0.06 to 0.15 mm
Supply Method	Easy Paper Loading	Easy Paper Loading
Physical Characteristics		
Dimensions (W x L x H)	144 x 185 x 206 mm (5.67 x 7.28 x 8.11 inch)	144 x 158 x 210 mm (5.67 x 6.22 x 8.27 inch)
Weight	2.20 kg (4.85 lbs.)	2.00 kg (4.40 lbs.)
Electrical	EnergyStar® Certified, External Power Supply Housed Internally (Adapter 24 V/2.5 A)	EnergyStar® Certified, External Power Supply Housed Internally (Adapter 24 V/2.5 A)
Display	2-inch Colour TFT LCD	2-inch Colour TFT LCD
Drawer Port	2 ports (Via Y-Type Adapter)	2 ports (Via Y-Type Adapter)
Performance Characteristics		
Memory	512 MB SDRAM, 256 MB Flash	128 MB SDRAM,256 MB Flash Optional 256 MB SDRAM, 512 MB Flash
NV Image Memory	1024 Kbytes	768 Kbytes (Mono)
Receive Buffer	4 Kbytes	4 Kbytes
User Define Buffer	12 Kbytes	12 Kbytes
Interface	Standard: USB 2.0 HS + Ethernet Optional: ① Standard + Bluetooth® ② Standard + WLAN ③ Standard + Powered USB ④ Standard + Serial WLAN: 802.11a//b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP)	SRP-S300Standard: USB 2.0 FS Optional: ① USB 2.0 FS + Serial ② USB 2.0 FS + Parallel ④ USB 2.0 FS + WLAN[1] ⑤ USB 2.0 FS + Bluetooth® SRP-S320 Standard: USB 2.0 FS + Ethernet Optional: ① USB 2.0 FS + Ethernet + Serial ② USB 2.0 FS + Ethernet + WLAN[1] ③ USB 2.0 FS + Ethernet + Bluetooth SRP-S300Hi, 320Hi (B-gate Hub Interface): 3 USB Type-A (Host, 2.0 HS) + 1 USB Type-A (Charging only) + 1 USB Type-B (2.0 HS) + Ethernet + WLAN[2] WLAN[1]: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) WLAN[2]: 802.11a/b/g/n/ac USB dongle type (Optional)
Environment Characteristics		
Temperature	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 10 to 90% RH	Operating: 10 to 80% RH Storage: 10 to 90% RH
Sealing	IP22	IP23
Software		
Emulation	BXL/POS™	BXL/POS™, SLCS™, BPL-Z™ (ZPL II®), BPL-C™ (CPCL)
Driver / Utility	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program Network Auto Installer	BXL/POS - Windows® Driver, OPOS/JPOS Driver, Linux®/macOS® CUPS Driver, Virtual COM USB/Ethernet Driver, Utility Program, Network Auto Installer SLCS, BPL-Z, BPL-C - Windows Driver (Europlus/Seagull), OPOS/JPOS Driver, Linux/Mac CUPS Driver, Virtual COM USB/Ethernet Driver, Utility Program, Label Artist-II™, Device Driver for SAP®
Developer Tools	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK B-gate SDK_Cloud Server Print B-gate SDK_Web App Print	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK
Design & Print	mPrint App (Android/iOS) POS Artist™ (Windows)	BXL/POS-mPrint App (Android/iOS), SLCS, BPL-Z BPL-C mPrint App (Android/iOS), Label Artist™ Mobile (Android/iOS), BarTender® Ultralite for BIXOLON POS Artist™ (Windows)
MDM (Optional)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android)
Fonts/Graphics/Symbologies		
Character Size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24	BXL/POS Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24 SLCS, BPL-Z, BPL-C Bitmap Fonts (10 SLCS, 16 BPL-Z), Scalable Fonts (1 SLCS, 1 BPL-Z, 7 BPL-C), 23 Code page, Unicode Supported (UTF-8, UTF-16LE, UTF-16BE)
Characters per Line	Font A: 48, Font B, C: 64	Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 33 page International: 32	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32
Barcode Symbologies	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, GS1-128, GS1 DataBar Stacked/ Omnidirectional/ Truncated/ Limited/ Expanded, PDF417, QR code	BXL/ POS 1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E / 2D: Data Matrix, PDF417, QR code SLCS, BPL-Z, BPL-C 1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39
Accessories / Supplies / Warranty		
Included in the Box	Power Cord, USB A-B Cable 1.8 m	AC/DC Adapter, Power Cord, 2-inch Partition (40/58 mm), USB A-B Cable 1.8 m
Options & Accessories	External Buzzer, B-Melodist, Powered USB (0.5/1.2 m), Serial Cable (9-9/25-9 pin),	Serial Cable (9-9 pin)
Compatible Supplies	B-linerless™	B-linerless™
Warranty	2 Years	2 Years





	SRP-G300	SRP-275III
Print Characteristics		
Print Method	Direct Thermal	9 Pin Serial Dot Matrix
Print Speed	Up to 255 mm/sec	Up to 5.1 lps (at 40 colums)
Print Resolution	203 dpi (8 dots/mm)	80 dpi (Horizontal) 144 dpi (Vertical)
Print Width	80 mm	Up to 63.5 mm
Printing Format	Normal, Height And Width From 1x to 8x, Reverse, Underlined	-
Printing Direction	Straight, 90°, 180°, 270°	-
Sensor	TPH Temperature, Paper End, Cover Open, Black Mark, Paper Near End, Paper Jam, Stacker Position, Stacker Full	Paper End, Paper Near End, Wall Mounting Paper Near End, Rear Cover Open, Black Mark
Media Characteristics		
Media Type	Receipt, Ticket	Receipt
Media Width	82.5 mm	76.5 mm
Media Roll Diameter	Up to 203 mm	Up to 83 mm
Media Thickness	0.06 to 0.09 mm	0.06 to 0.085 mm
Media Weight	from 50 to 90g/m²	-
Supply Method	Easy Paper Loading	Easy Paper Loading
Physical Characteristics		
Dimensions (W x L x H)	154 x 373 x 251 mm (6.06 x 14.69 x 9.88 inch)	160 x 239 x 157 mm (6.29 x 9.40 x 6.18 inch)
Weight	3 kg (6.61 lbs.)	A: 2.4 kg (5.29 lbs.) C: 2.5 kg (5.51 lbs.)
Electrical	USB (Internal Power Adapter): EnergyStar® Certified, External Power Supply Housed Internally, 100 to 240V, 1.5A, 50/60Hz Powered USB: 24Vdc, 2.5A	EnergyStar® Certified, External Power Supply Housed Internally (Adapter 24V/2.5A), 50/60Hz
Medium Consumption	1.8 A	-
Drawer Port	2 ports (Via Y-Type Adapter)	2 ports (Via Y-Type Adapter)
Performance Characteristics		
Memory	16 MB SDRAM, 16 MB Flash	-
NV Image Memory	-	256 Kbytes (Mono)
Graphic Memory	1 MB	-
Data Buffer	256 Kbytes	-
Receive Buffer	64 Kbytes	64 Kbytes
User Define Buffer	12 Kbytes	64 Kbytes
Interface	Standard: USB 2.0 FS Optional: Powered USB	① USB 2.0 FS + Serial + Ethernet* ② USB 2.0 FS + Parallel ③ USB 2.0 FS + Serial * DHCP enabled
Environment Characteristics		
Temperature	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60°C (-4 to 140°F)
Humidity	Operating: 10 to 80% RH Storage: 10 to 90% RH	Operating: 10 to 80% RH Storage: 10 to 90% RH
Software		
Emulation	BXL/POS™	BXL/POS™
Driver / Utility	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB Driver Utility Program	Windows® Driver OPOS/JPOS Driver Linux®/macOS® CUPS Driver Virtual COM USB/Ethernet Driver Utility Program
Developer Tools	Android™/Windows SDK Linux SDK Xamarin® SDK (Android) Web Print SDK (Windows/Android) Cordova™ Plugin (Android) MAUI SDK (Android) Flutter™ Plugin (Android) React Native® SDK (Android)	Android™/iOS®/Windows SDK Linux SDK Xamarin® SDK Web Print SDK (Android/iOS/Windows/macOS) Cordova™ Plugin MAUI SDK Flutter™ Plugin React Native® SDK
Design & Print	mPrint App (Android)	-
MDM (Optional)	-	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android)
Fonts / Graphics / Symbologies		
Character Size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24	Font A: 9 x 9, Font B: 7 x 9, KOR: 17 x 9, CHN: 16 x 16
Characters per Line	Font A: 53, Font B, C: 71	Font A: 35 Font B: 40 KOR: 20 CHN: 22
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 37 page International: 32	-
Barcode Symbologies	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, UPC-A, UPC-E , ITF, RSS 2D: Data Matrix, PDF417, QR code, Aztec, MaxiCode, GS1-128, GS1 DataBar Stacked, Omnidirectional, Truncated, Limited, Expanded	-
Accessories / Supplies / Warranty		
Included in the Box	Power Cord, USB A-B Cable 1.8 m	Paper, AC Adapter, Power cord, Ribbon cassette
Options & Accessories	Powered USB (0.5/1.2 m)	Wall Mount, Splash Proof Cover, Ribbon Cartridge, B-Melodist, Exernal Buzze, USB A-B Cable 1.8m
Warranty	2 Years	2 Years



Comparison Table of Linerless Printers

	SRP-S3000X	SRP-S3000	SRP-S300IIX	SRP-S300II	SRP-S300 Series				SRP-S200
					SRP-S300TX, SRP-S320TX	SRP-S300T	SRP-S300LX	SRP-S300L	
Taken Sensor	•	•	•	•	•		-		•
Linerless Restick	•	•	•	•	•	•	•	•	•
Linerless Permanent	•	-	•	-	•	-	•	-	-
Liner Label	•	•	-	-	-	-	-	-	-

Comparison Table of SRP-Q300 Series

	SRP-Q300II	SRP-Q300	SRP-Q300B	SRP-QE300
				
Description	Advanced Cube Printer	Cube Printer	Cube Printer with Battery	Economic Cube Printer
Paper Width	80 mm or 58 mm (3-inch or 2-inch)			
Dimension	128 x 125 x 125 mm (5.03 x 4.92 x 4.92 inch)		128 x 125 x 169.2 mm (5.03 x 4.92 x 6.66 inch)	128 x 125 x 125 mm (5.03 x 4.92 x 4.92 inch)
Speed	250 mm /sec	220 mm /sec		200 mm /sec
Interface	3 USB Type-A (Host) + 1 USB Type-B + 1 USB Type-C® + Ethernet + optional WLAN or Bluetooth®	USB Type-B + Ethernet + USB Type-A (Charging only) + optional WLAN or Bluetooth		USB + Ethernet
Charging	Yes (Power Delivery Supported)	Yes	Yes	No
Network Tethering	Yes	No		
USB Ports with Peripheral Device Support	Yes	No		
Web & Cloud Printing	Yes	No	No	No
NFC	No	Yes	Yes	No
Unicode	No	Yes	Yes	No
BCD-3000	No	Yes	Yes	No

Interface Card Reference

Model	On Board	Serial		Parallel	USB	Ethernet	Bluetooth	WLAN		B-gate
		IFJ-SD	IFJ-S	IFJ-P	IFJ-PW	IFJ-EL	IFJ-Ba	IFJ-WDa	IFJ-WDb	IFJ-BGT
SRP-350III	USB	•	•	•						
SRP-350plusV	USB, Ethernet	•	•	•	•		•	•		
SRP-350V	USB	•	•	•		•				
SRP-380	USB	•	•			•	•	•		
SRP-380plus	USB, Ethernet	•	•	•	•		•	•		
SRP-F310II	USB, Ethernet	•	•	•			•	•		•
SRP-S300	USB	•	•	•			•	•		•
SRP-S300II	USB, Ethernet		•		•		•		•	



	BCD-2000	BCD-3000
Display		
Display Method	STN LCD	STN LCD
Display Colour Background / Text (Image)	Blue/White	Blue/White
Active Area (W) x (H) mm	118.5 x 45.5	96 x 19.2
Visual Area (W) x (H) mm	127.2 x 33.9	99 x 24
Brightness (cd/m²)	100	100
Character Number (Letters) x (Lines)	30 x 4	20 x 2
Character Type(Set)	95 Alphanumeric, 6 International	95 Alphanumeric, 6 International
Character Pattern (W) x (H) dot	8 x 16, 9 x 17	8 x 16
Character Size (W) x (H) mm	4.24 x 8.48	4.8 x 9.6
Character Space (mm)	0.03	0.05
Receive Buffer (byte)	1K	1K
Emulation	BXL/POS™, CD5220, UTC Enhance, UTC Standard, PD6000	BXL/POS™, CD5220, UTC Enhance, UTC Standard, PD6000
Electrical		
Electrical – Voltage	USB: 5VDC ± 5% (USB Bus Power) RS232: 5VDC to 24VDC	USB: 5VDC ± 5% (USB Bus Power) RS232: 5VDC ± 5%
Electrical – Current	500mA	500mA
Interface	RS232/USB	RS232 (for SRP-Q300 only) / USB
Software		
Driver	Windows® Driver, OPOS Driver	Windows Driver®, OPOS Driver
Developer Tools	Android™ SDK, iOS® SDK	Windows SDK, Android™ SDK, iOS® SDK
Exterior		
Body Colour	Ivory/Dark-Gray	Ivory/Black
Rotation Angle	Horizontal: +/-180° Vertical: 52° (5 positions)	Vertical: 35°
Overall Dimension (W x L x H) mm	BCD-2000A,AU: 162.5 x 97.6 x 167 to 521 BCD-2000N,NU: 161 x 75.8 x 153 to 507 BCD-2000DS: 220.4 x 105.4 x 174 to 528 BCD-2000WA,WAU: 162.5 x 166 x 189 BCD-2000WN,WNU: 161 x 152 x 178 BCD-2000WS: 220.4 x 173 x 193	130 x 110.3 x 68.5
Product weight (g)	850	250
Enviroment & Reliability / Warranty		
Operating Temperature	0 to 40 / 32 to 104	0 to 40 / 32 to 104
Operating Humidity	10 to 80	10 to 80
Storage Temperature	-20 to 55 / -4 to 131	-20 to 55 / -4 to 131
Storage Humidity	10 to 90	10 to 90
Reliability (Display) (hours)	50,000 (Backlight)	50,000 (Backlight)
Warranty	2 Years	2 Years





		BK3-21	BK3-31 Series
Print Characteristics			
Print Method		Direct Thermal	Direct Thermal
Print Speed		Up to 250 mm/sec	Up to 250 mm/sec
Print Resolution		203 dpi	203 dpi
Print Width		12/48/54 mm	12/48/54/72 mm
Sensor		Paper End, Cover Open, Near End, Black Mark	Paper End, Cover Open, Near End, Black Mark
Media Characteristics			
Media Type		Receipt	Receipt
Media Width		20/58/60 mm	20/58/60/80/83 mm
Media Roll Diameter		80/102/120 mm	BK3-31,34: 80/102/120/150 mm BK3-32: Up to 250 mm BK3-33: Up to 83 mm
Media Thickness		0.05 to 0.12 mm	0.05 to 0.12 mm
Supply Method		Easy Paper Loading	Easy Paper Loading
Physical Characteristics			
Dimensions (W x L x H)		BK3-21 Media Roll Diameter Φ80: 109 x 130 x 91 mm Media Roll Diameter Φ102: 109 x 137 x 99 mm Media Roll Diameter Φ120: 109 x 144 x 105 mm BK3-21 (Vertical) Media Roll Diameter Φ80: 109 x 160 x 91 mm Media Roll Diameter Φ102: 109 x 167 x 99 mm Media Roll Diameter Φ120: 109 x 173 x 105 mm	BK3-31,34 Media Roll Diameter Φ80: 130 x 130 x 91 mm Media Roll Diameter Φ102: 130 x 137 x 99 mm Media Roll Diameter Φ120: 130 x 144 x 105 mm Media Roll Diameter Φ150: 130 x 160 x 105 mm BK3-31,34 (Vertical) Media Roll Diameter Φ80: 130 x 159 x 91 mm Media Roll Diameter Φ102: 130 x 167 x 99 mm Media Roll Diameter Φ120: 130 x 173 x 105 mm Media Roll Diameter Φ150: 130 x 189 x 105 mm BK3-32 Media Roll Diameter Φ250: 130 x 339 x 145 mm BK3-33 Media Roll Diameter Φ83: 130 x 137 x 96 mm
Weight		600 g	BK3-31,33,34: 700 g BK3-32: 1,470 g
Electrical		100-240 VAC, 50/60 Hz, 24V	100-240 VAC, 50/60 Hz, 24V
Lever Direction		Right	Left, Right
Mount Direction		Horizontal/Vertical	BK3-31,34: Horizontal/Vertical BK3-32,33: Horizontal
Performance Characteristics			
NV Image Memory		256 Kbytes (Mono)	256 Kbytes (Mono)
Receive Buffer		64 Kbytes	64 Kbytes
User Define Buffer		12 Kbytes	12 Kbytes
Interface		USB V2.0 FS+ Serial	Standard: USB V2.0 FS + Serial Optional: USB V2.0 FS + Serial + Ethernet
Connector Type	Power	DC-Jack or 2P Connector	DC-Jack or 2P Connector
	USB	USB B type (Default)	USB B or 4P Connector
	Serial	9P Male or 5P Connector	9P Male or 5P Connector
Environment Characteristics			
Temperature		Operating: -20 to 60 °C (-4 to 140 °F) * Optimal printing performances and maximum reliability will be obtained between 0 and 40 °C Storage: -20 to 60 °C (-4 to 140 °F)	Operating: -20 to 60 °C (-4 to 140 °F) * Optimal printing performances and maximum reliability will be obtained between 0 and 40 °C Storage: -20 to 60 °C (-4 to 140 °F)
Humidity		Operating: 10 to 95 % (non-condensing) Storage: 10 to 95 % (non-condensing) excluding paper	Operating: 10 to 95 % (non-condensing) Storage: 10 to 95 % (non-condensing) excluding paper
Software			
Emulation		BXL/POS™	BXL/POS™
Driver / Utility		Windows Driver®, OPOS/JPOS Driver, Linux®/macOS® CUPS Driver, Utility Program, Network Auto Installer	Windows Driver®, OPOS/JPOS Driver, Linux®/macOS® CUPS Driver, Utility Program, Network Auto Installer
Developer Tools		Android™ SDK, Windows SDK, Linux SDK	Android™ SDK, Windows SDK, Linux SDK
Fonts / Graphics / Symbologies			
Character Size		Font A: 12×24 Font B: 9×17 Font C: 9×24 KOR, CHN, JPN: 24x24	Font A: 12×24 Font B: 9×17 Font C: 9×24 KOR, CHN, JPN: 24x24
Characters per Line (Paper Width)		Print width 12 mm: Font A: 8 Font B, C: 10, KOR, CHN, JPN: 4 Print width 48 mm: Font A: 32 Font B, C: 42, KOR, CHN, JPN: 16 Print width 54 mm: Font A: 36 Font B, C: 48, KOR, CHN, JPN: 18	Print width 12 mm: Font A: 8 Font B, C: 10, KOR, CHN, JPN: 4 Print width 48 mm: Font A: 32 Font B, C: 42, KOR, CHN, JPN: 16 Print width 54 mm: Font A: 36 Font B, C: 48, KOR, CHN, JPN: 18 Print width 72 mm: Font A: 48 Font B, C: 64, KOR, CHN, JPN: 24
Character Sets		Alphanumeric: 95 Extended Graphics: 128×35 page International: 32	Alphanumeric: 95 Extended Graphics: 128×35 page International: 32
Graphics		Supporting user-defined fonts, graphics, formats and logos	Supporting user-defined fonts, graphics, formats and logos
Barcode Symbologies		1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, GS1-128, GS1 DataBar Stacked/ Omnidirectional/ Truncated/Limited/Expanded, PDF417, QR code	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, GS1-128, GS1 DataBar Stacked/ Omnidirectional/Truncated/Limited/Expanded, PDF417, QR code
Accessories / Supplies / Warranty			
Accessories		AC/DC Adapter (DC Jack), AC/DC Adapter (2P Connector), Male to Male type Serial Cable,5P to Male type Serial Cable,USB A-B Cable 1.8 m, Power Cord	AC/DC Adapter (DC Jack), AC/DC Adapter (2P Connector), Male to Male type Serial Cable,5P to Male type Serial Cable,USB A-B Cable 1.8 m, Power Cord
Warranty		2 Years	2 Years
Options			
Bezel	Type	Non-Bezel / Standard-Bezel (4 types)	Non-Bezel / Standard-Bezel (4 types) / LED-Bezel (Green)
Presenter (LED-Bezel default)	Paper Stock Direction	-	Upper
	Media Width	-	80 mm
	Media Thickness	-	0.05 to 0.10 mm
	Media Length	-	50 to 250 mm
	Ejection Speed	-	Up to 250 mm/sec
Retractor (BK5-31: for ticket printing only)	Paper Stock Direction	-	Upper
	Media Width	-	58/80 mm
	Media Thickness	-	0.05 to 0.10 mm
	Media Length	-	70 to 350 mm
	Ejection & Retractor Speed	-	Up to 500 mm/sec
	Basic Movement	-	Retraction, Clamp, Continuous





		BK5-31	BK5-41
Print Characteristics			
Print Method		Direct Thermal	Direct Thermal
Print Speed		Up to 150 mm/sec	Up to 150 mm/sec
Print Resolution		203 dpi	203 dpi
Print Width		12/48/54/72/80 mm	12/48/54/72/80/104/108mm
Sensor		Paper End, Cover Open, Near End, Black Mark, Gap Sensor	Paper End, Cover Open, Black Mark, Gap Sensor
Media Characteristics			
Media Type		Ticket, Label (Gap, Black Mark)	Ticket, Label (Gap, Black Mark)
Media Width		20/58/60/80/83 mm	20/58/60/80/83/108/118mm
Media Roll Diameter		130/150 mm	130 mm
Media Thickness		Width 80/83 mm: 0.1 to 0.15 mm Width 20/58/60 mm: 0.1 to 0.20 mm	0.1 to 0.15 mm
Supply Method		Easy Paper Loading	Easy Paper Loading
Physical Characteristics			
Dimensions (W x L x H)		BK5-31 Media Roll Diameter Φ130: 130 x 181 x 123 mm Media Roll Diameter Φ150: 130 x 188 x 130 mm	167 x 185 x 124 mm
Weight		780 g	900g
Electrical		100-240 VAC, 50/60 Hz, 24V	100-240 VAC, 50/60 Hz, 24V
Lever Direction		Right	Right
Mount Direction		Horizontal	Horizontal
Performance Characteristics			
NV Image Memory		256 Kbytes (Mono)	256 Kbytes (Mono)
Receive Buffer		64 Kbytes	64 Kbytes
User Define Buffer		12 Kbytes	12 Kbytes
Interface		USB V2.0 FS+ Serial	USB V2.0 FS+ Serial
Connector Type	Power	DC-Jack or 2P Connector	DC-Jack
	USB	USB B type or 4P Connector	USB B type
	Serial	9P Male or 5P Connector	9P Male
Environment Characteristics			
Temperature		Operating: -20 to 60 °C (-4 to 140 °F) * Optimal printing performances and maximum reliability will be obtained between 0 and 40 °C Storage: -20 to 60 °C (-4 to 140 °F)	Operating: 0 to 40°C (32 to 104°F) Storage: -20 to 60 °C (-4 to 140 °F)
Humidity		Operating: 10 to 95 % (non-condensing) Storage: 10 to 95 % (non-condensing) excluding paper	Operating: 10 to 80 % (non-condensing) Storage: 10 to 95 % (non-condensing) excluding paper
Software			
Emulation		BXL/POS™	BXL/POS™
Driver / Utility		Windows® Driver, OPOS/JPOS Driver, Linux®/macOS® CUPS Driver, Utility Program	Windows® Driver, OPOS/JPOS Driver, Linux®/macOS® CUPS Driver, Utility Program
Developer Tools		Android™ SDK, Windows SDK, Linux SDK, Web Print SDK (Windows/Android)	Android™ SDK, Windows SDK, Linux SDK, Web Print SDK (Windows/Android)
Fonts / Graphics / Symbologies			
Character Size		Font A: 12×24 Font B: 9×17 Font C: 9×24 KOR, CHN, JPN: 24x24	Font A: 12×24 Font B: 9×17 Font C: 9×24 KOR, CHN, JPN: 24x24
Characters per Line (Paper Width)		Print width 12 mm: Font A: 8 Font B, C: 10, KOR, CHN, JPN: 4 Print width 48 mm: Font A: 32 Font B, C: 42, KOR, CHN, JPN: 16 Print width 54 mm: Font A: 36 Font B, C: 48, KOR, CHN, JPN: 18 Print width 72 mm: Font A: 48 Font B, C: 64, KOR, CHN, JPN: 24	Print width 12 mm: Font A: 8 Font B, C: 10, KOR, CHN, JPN: 4 Print width 48 mm: Font A: 32 Font B, C: 42, KOR, CHN, JPN: 16 Print width 54 mm: Font A: 36 Font B, C: 48, KOR, CHN, JPN: 18 Print width 72 mm: Font A: 48 Font B, C: 64, KOR, CHN, JPN: 24 Print width 80 mm: Font A: 53 Font B, C: 71, KOR, CHN, JPN: 26 Print width 104 mm: Font A: 69 Font B, C: 92, KOR, CHN, JPN: 34 Print width 108 mm: Font A: 72 Font B, C: 96, KOR, CHN, JPN: 36
Character Sets		Alphanumeric: 95 Extended Graphics: 128×35 page International: 32	Alphanumeric: 95 Extended Graphics: 128×35 page International: 32
Graphics		Supporting user-defined fonts, graphics, formats and logos	Supporting user-defined fonts, graphics, formats and logos
Barcode Symbologies		1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, GS1-128, GS1 DataBar Stacked/ Omnidirectional/Truncated/Limited/Expanded, PDF417, QR code	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, GS1-128, GS1 DataBar Stacked/ Omnidirectional/Truncated/Limited/Expanded, PDF417, QR code
Accessories / Supplies / Warranty			
Accessories		AC/DC Adapter (DC Jack), AC/DC Adapter (2P Connector),Male to Male type Serial Cable, 5P to Male type Serial Cable,USB A-B Cable 1.8 m, Power Cord	AC/DC Adapter (DC Jack), Male to Male type Serial Cable,USB A-B Cable 1.8 m, Power Cord
Warranty		2 Years	2 Years
Options			
Bezel	Type	Non-Bezel / Standard-Bezel (4 types)	-
Presenter (LED-Bezel default)	Paper Stock Direction	-	-
	Media Width	-	-
	Media Thickness	-	-
	Media Length	-	-
	Ejection Speed	-	-
Retractor (BK5-31: for ticket printing only)	Paper Stock Direction	Upper	-
	Media Width	58/60/80 mm	-
	Media Thickness	0.10 to 0.15 mm	-
	Media Length	70 to 350 mm	-
	Ejection & Retractor Speed	Eject: Up to 150 mm/sec Retractor: Up to 500 mm/sec	-
	Basic Movement	Retraction, Continuous	-

B-linerless™

B-linerless labels are a labelling solution that does not require a silicone liner, resulting in no liner backing waste. Enabling variable-length labelling, they are available in two different adhesive strengths - B-linerless Restick and B-linerless Permanent to suit a wide range of applications.



Product Line		B-linerless Restick			B-linerless Permanent			
Model Name		TS40	TS58	TS80	PS40	PS58	PS80	PS105
Dimensions of the Product	width (mm)	40	58	80	40	58	80	105
	length (m)	75	75	75	75	75	75	100
Number of Rolls in a Carton Box		32	20	16	32	20	16	12
Roll Diameter (mm)		100	100	100	100	100	100	115
Inner Core Diameter (inch)		1	1	1	1	1	1	1
Applicable Models		B-linerless Restick			B-linerless Permanent			
		TS40	TS58	TS80	PS40	PS58	PS80	PS105
SRP-S200		●	●	-	-	-	-	-
SRP-S300T/L		●	●	●	-	-	-	-
SRP-S300TX/LX		-	-	-	●	●	●	-
SRP-S320		-	-	-	●	●	●	-
SRP-S300IIX		●	●	●	●	●	●	-
SRP-S300II		●	●	●	-	-	-	-
SRP-S3000		●	●	●	-	-	-	-
SRP-S3000X		-	-	-	●	●	●	-
XL5-40		-	-	-	-	-	-	●



B-post Label™

B-post Label is a label solution featuring an adhesive-free black mark on the reverse of the label for printing labels of various sizes within the Postal Industry.

MDM

XPM™, XCM™

BIXOLON's web-based XPM™ software enables remote management of registered printer fleets through major browsers, offering centralised configuration, firmware updates, and real-time monitoring across wired and wireless networks. XCM™ is an agent App that enables non-network interface models and locally connected printers to communicate with the XPM™ server, extending centralised management to printers without direct network connectivity.

SOTI Connect

SOTI Connect is an enterprise-grade printer management solution that provides an organization complete lifecycle management of its mobile and industrial printers. BIXOLON provides a wide range of Label Printers certified with SOTI Connect, providing you with business-critical printer identification and management.

DESIGN & PRINT

Label Artist™ Web

BIXOLON Label Artist™ Web allows users to easily design and print labels directly to BIXOLON mobile, desktop, or industrial printers from any device or platform. Supporting Windows®, Mac® PCs, iOS™ and Android™ mobile devices, as well as Chrome, and Microsoft Edge and Safari, it also provides access to external databases and cloud storage. Accessible through labelartist.bixolon.com on a PC or is available to download on a mobile via the App Store® or Google Play™.

Label Artist™ Mobile

BIXOLON Label Artist™ Mobile allows users to easily edit and print labels from their chosen iOS™ or Android™ device to BIXOLON mobile and desktop label printers using Bluetooth® or WLAN. A USB connection is also supported for Android™ devices.

Label Artist-II™

BIXOLON Label Artist™ helps users to create their own label design on Windows PCs and print it with our Industrial, Desktop and Mobile Label printers via USB. Providing ability to connect databases and create images, multi-text and barcodes. While also easily setting printing preferences such as media type, print direction and cutting option, Label Artist™ offers perfect label customisation.

Windows POS Artist

BIXOLON's Windows POS Artist enables users to fully customise receipts by creating designs on a Windows PC and printing directly to BIXOLON POS printers via multiple interfaces. It supports database connections, image creation, multi-text and barcode printing, while allowing easy configuration of media type, print direction, and cutting options.

mPrint

The BIXOLON mPrint app allows users to print images and PDF documents directly from iOS™ or Android™ devices to BIXOLON printers. It also supports printing from web browsers, such as Google Chrome or Safari and any app with a share function. Connections via Bluetooth, Wi-Fi, Ethernet and USB for Android™ devices, providing versatile, convenient printing options.

Food Labelling App

BIXOLON offers a free, easy-to-use Food Labelling App designed for use with the XQ-840II 8-inch Android tablet embedded label printer. The software enables restaurants and supermarkets to produce food labels on demand, including expiration dates, nutritional information, ingredients and other essential food labelling details.

DEVELOPER TOOLS

Web Print SDK

Web Print SDK provides a set of Javascript APIs businesses can utilise to build a browser-based, multi-platform solutions which enables direct printing from Windows®, Android™ and Apple iOS™, macOS® platformed web browsers to BIXOLON printers.

XI

BIXOLON's BASIC programming language interpreter, XI enables standalone label printing without an accompanying PC. XI allows users to develop applications(.BAS) with BASIC to enable BIXOLON printers to create labels with input data directly received from peripherals such as a barcode scanner, electronic scale via USB connection.

DRIVER

SAP

Device Driver for SAP®

BIXOLON Device Driver for SAP® allows direct printing from the SAP Smart Forms to a selection of BIXOLON label printers without additional software or middleware and ensuring seamless, efficient, and reliable label production within SAP environments.

Windows

Window Driver

BIXOLON's Windows driver enables seamless printing to our POS, Mobile, and Label printers across Windows' operating system. The Windows POS Driver Status Monitor provides real-time, multi-driver status visibility and offers advanced tools that help enhance overall print quality.

UTILITY

BIXOLON Mobile Utility

BIXOLON Utility is a free-of-charge mobile application supporting useful printer setup including wireless connectivity, printer configuration, RFID, and more. Alongside, BIXOLON's SWC (Simple Wi-Fi Connect) function is supported by Android devices.

Network Auto Installer

Simplifying setup procedures, Network Auto Installer supports a one-click-installation of printer drivers by automatically detecting and retrieving the IP information of active printers currently connected to the same network as the host device. Designed for printers in Windows based environments.

		Mobile								Label										
		SPP-C200	SPP-C300	SPP-R200III	SPP-R310	SPP-R410	SPP-L310	SPP-L410	XM7 Series	SLP-DL410 Series	XD3-40 Series	SLP-DX220	SLP-TX220	XD5-40 Series	XD5-40II Series	XD7-20d	XQ-840II	XL5-40	XT3-40	XT5-40 Series
Windows™ Driver	Windows Server 2008 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows Server 2008 R2 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows 7 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows 8 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows Server 2012 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows 10 32bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows 11 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
OPOS Driver	Windows Server 2008 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows Server 2008 R2 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows 7 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows 8 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows Server 2012 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows 10 32bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows 11 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
JPOS Driver	Windows 7 32 bit / 64 bit	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
	Windows 8 32 bit / 64 bit	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
	Windows 10 32bit / 64 bit	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
	Windows 11 64 bit	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
	Linux Kernel 2.6.32 and later	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
Linux CUPS Driver	Linux Kernel 2.6.32 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
Linux SDK	Linux Kernel 2.6.32 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
macOS Driver	macOS X 10.7, 10.8	●	●	●	●	●	●	●	●	●	●	●	●	●				●		●
	macOS X 10.9	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	macOS X 10.10 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
Virtual COM Driver	Virtual COM USB Driver	●	●				●	●	●	●	●	●	●	●	●	●		●	●	●
	Virtual COM Ethernet Driver									●	●	●	●	●	●	●		●	●	●
Web Print SDK	Windows XP 32 bit / 64 bit	●	●	●	●	●			●	●		●	●	●	●	●		●	●	●
	Windows VISTA 32 bit / 64 bit	●	●	●	●	●			●	●		●	●	●	●	●		●	●	●
	Windows 7 32 bit / 64 bit	●	●	●	●	●			●	●		●	●	●	●	●		●	●	●
	Windows 8 32 bit / 64 bit	●	●	●	●	●			●	●		●	●	●	●	●		●	●	●
	Windows 10 32bit / 64 bit	●	●	●	●	●			●	●		●	●	●	●	●		●	●	●
	Windows 11 64 bit	●	●	●	●	●			●	●		●	●	●	●	●		●	●	●
	Android 6.0 and later	●	●	●	●	●			●	●		●	●	●	●	●		●	●	●
	iOS 15.0 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	macOS 10.15 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
iOS® SDK	iOS 15.0 and later	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
Android™ SDK	Android 2.3 and later																			
	Android 3.1 and later						●	●	●	●		●	●	●				●	●	●
	Android 3.2 and later																			
	Android 6.0 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Windows SDK	Windows XP 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows Server 2003 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows VISTA 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows Server 2008 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows Server 2008 R2 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows 7 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows 8 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows Server 2012 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows 10 32bit / 64bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
	Windows 11 64bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
Windwos SDK (CE/Mobile)	Windows CE 5.0 and later	●	●	●	●	●	●	●	●	●		●	●	●				●	●	●
	Windows Mobile 5.0 and later	●	●	●	●	●	●	●	●	●		●	●	●				●	●	●
Xamarin / MAUI SDK	Windows 10 32 bit / 64 bit	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
	Windows 11 64 bit	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
	Android 6.0 and later	●	●	●	●	●	●	●	●	●		●	●	●	●	●	●	●	●	●
	iOS 15.0 and later	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
Cordova Plugin	Windows 10 32 bit / 64 bit	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
	Android 6.0 and later	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
	iOS 15.0 and later	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
React Native SDK	Windows 10 build 14393 or later	●	●	●	●	●	●	●	●	●		●	●	●	●	●		●	●	●
	Android 6.0 and later	●	●	●	●	●	●	●	●	●		●	●	●	●	●	●	●	●	●
	iOS 15.0 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
Flutter™ Plugin	Android 6.0 and later	●	●	●	●	●	●	●	●	●		●	●	●	●	●	●	●	●	●
	iOS 15.0 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
XPM™ (Optional)	Windows 10 64 bit			○	○	○	●	●	●	○		○	○	●	●	●		●	●	●
	Windows 11 64 bit			○	○	○	●	●	●	○		○	○	●	●	●		●	●	●
	Windows Server 2012 64 bit			○	○	○	●	●	●	○		○	○	●	●	●		●	●	●
	Windows Server 2016 64 bit			○	○	○	●	●	●	○		○	○	●	●	●		●	●	●
XCM™ (Optional)	Windows VISTA 32 bit / 64 bit	○	○	○	○	○	●	●	●	○		○	○	●	●	●		●	●	●
	Windows 7 32 bit / 64 bit	○	○	○	○	○	●	●	●	○		○	○	●	●	●		●	●	●
	Windows 8 32 bit / 64 bit	○	○	○	○	○	●	●	●	○		○	○	●	●	●		●	●	●
	Windows 10 32bit / 64bit	○	○	○	○	○	●	●	●	○		○	○	●	●	●		●	●	●
	Windows 11 64bit	○	○	○	○	○	●	●	●	○		○	○	●	●	●		●	●	●
	Android 6.0 and later	○	○	○	○	○	●	●	●	○		○	○	●	●	●	●	●	●	●
SOTI® Connect									●	●		●	●	●		●		●		●
Device Driver for SAP®							●	●	●			●	●	●	●	●		●	●	●
Label Artist-II™							●	●	●	●	●	●	●	●	●	●	●	●	●	●
Label Artist™ Mobile	Android 6.0 and later						●	●	●	●	●	●	●	●	●	●	●	●	●	●
	iOS 15.0 and later						●	●	●	●	●	●	●	●	●	●		●	●	●
Label Artist™ Web	Windows						●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Android 7.0 and later						●	●	●	●	●	●	●	●	●	●	●	●	●	●
	iOS 15.0 and later						●	●	●	●	●	●	●	●	●	●		●	●	●
BarTender® Ultralite for BIXOLON																				
POS Artist™	Windows 10 32bit / 64bit																			
	Windows 11 64bit																			
mPrint	Android 6.0 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	iOS 15.0 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●
XI (Optional)											○			○	○	○		○		○

		POS																			Kiosk		Display
		STP-103III	SRP-330III	SRP-350V	SRP-350plusV	SRP-380	SRP-380plus	SRP-F310II	SRP-Q200	SRP-QE300	SRP-Q300 Series	SRP-Q300II	SRP-S200	SRP-S300 Series	SRP-S300II	SRP-S3000	SRP-G300	SRP-275III	BK3 Series	BK5 Series	BCD-2000/3000
Windows™ Driver	Windows Server 2008 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows Server 2008 R2 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows 7 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows 8 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows Server 2012 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows 10 32bit / 64bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows 11 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
OPOS Driver	Windows Server 2008 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows Server 2008 R2 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows 7 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows 8 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows Server 2012 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows 10 32bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●			●	●	●	●	●	●	●	●	●
	Windows 11 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
JPOS Driver	Windows 7 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows 8 32 bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows 10 32bit / 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Windows 11 64 bit	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Linux Kernel 2.6.32 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Linux CUPS Driver	Linux Kernel 2.6.32 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Linux SDK	Linux Kernel 2.6.32 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
macOS Driver	macOS X 10.7, 10.8					●		●	●	●	●		●	●		●		●	●				
	macOS X 10.9	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●				
	macOS X 10.10 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			●	●			
Virtual COM Driver	Virtual COM USB Driver	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					●
	Virtual COM Ethernet Driver		●	●	●	●	●	●	●	●	●	●	●	●	●	●		●					
Web Print SDK	Windows XP 32 bit / 64 bit	●	●	●	●	●	●	●			●	●	●	●	●	●	●	●		●			
	Windows VISTA 32 bit / 64 bit	●	●	●	●	●	●	●			●	●	●	●	●	●	●	●		●			
	Windows 7 32 bit / 64 bit	●	●	●	●	●	●	●			●	●	●	●	●	●	●	●		●			
	Windows 8 32 bit / 64 bit	●	●	●	●	●	●	●			●	●	●	●	●	●	●	●		●			
	Windows 10 32bit / 64 bit	●	●	●	●	●	●	●			●	●	●	●	●	●	●	●		●			
	Windows 11 64 bit	●	●	●	●		●					●				●		●		●			
	Android 6.0 and later	●	●	●	●	●	●	●			●	●	●	●	●	●	●	●					
	iOS 15.0 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					
	macOS 10.15 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					
iOS® SDK	iOS 15.0 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					●
Android™ SDK	Android 2.3 and later	●																●					
	Android 3.1 and later	●																					●
	Android 3.2 and later	●																					
	Android 6.0 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
Windows SDK	Windows XP 32 bit / 64 bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●		
	Windows Server 2003 32 bit / 64 bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●		
	Windows VISTA 32 bit / 64 bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●		
	Windows Server 2008 32 bit / 64 bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●		
	Windows Server 2008 R2 64 bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●		
	Windows 7 32 bit / 64 bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●		
	Windows 8 32 bit / 64 bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●		
	Windows Server 2012 64 bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●		
	Windows 10 32bit / 64bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●		
	Windows 11 64bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●		
Windwos SDK (CE/Mobile)	Windows CE 5.0 and later			●												●							
	Windows Mobile 5.0 and later			●												●							
Xamarin / MAUI SDK	Windows 10 32 bit / 64 bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●							
	Windows 11 64 bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●							
	Android 6.0 and later		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
	iOS 15.0 and later		●	●	●	●	●	●	●	●	●	●	●	●	●	●							
Cordova Plugin	Windows 10 32 bit / 64 bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●							
	Android 6.0 and later		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					
	iOS 15.0 and later		●	●	●	●	●	●	●	●	●	●	●	●	●	●		●					
React Native SDK	Windows 10 build 14393 or later		●	●	●	●	●	●	●	●	●	●	●	●	●	●							
	Android 6.0 and later		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					
	iOS 15.0 and later		●	●	●	●	●	●	●	●	●	●	●	●	●	●		●					
Flutter™ Plugin	Android 6.0 and later		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					
	iOS 15.0 and later		●	●	●	●	●	●	●	●	●	●	●	●	●	●		●					
XPM™ (Optional)	Windows 10 64 bit				●	●	●	●			●	●	●	●	●	●	●						
	Windows 11 64 bit				●	●	●	●			●	●	●	●	●	●	●						
	Windows Server 2012 64 bit				●	●	●	●			●	●	●	●	●	●	●						
	Windows Server 2016 64 bit				●	●	●	●			●	●	●	●	●	●	●						
XCM™ (Optional)	Windows VISTA 32 bit / 64 bit				●	●	●	●			●	●	●	●	●	●	●						
	Windows 7 32 bit / 64 bit				●	●	●	●			●	●	●	●	●	●	●						
	Windows 8 32 bit / 64 bit				●	●	●	●			●	●	●	●	●	●	●						
	Windows 10 32bit / 64bit				●	●	●	●			●	●	●	●	●	●	●						
	Windows 11 64bit				●	●	●	●			●	●	●	●	●	●	●						
	Android 6.0 and later				●	●	●	●			●	●	●	●	●	●	●						
SOTI® Connect																							
Device Driver for SAP®																	●						
Label Artist-II™																							
Label Artist™ Mobile	Android 6.0 and later																						
	iOS 15.0 and later																						
Label Artist™ Web	Windows																						
	Android 7.0 and later																						
	iOS 15.0 and later																						
BarTender® Ultralite for BIXOLON																	●						
POS Artist™	Windows 10 32bit / 64bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●			
	Windows 11 64bit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●			
mPrint	Android 6.0 and later	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
	iOS 15.0 and later		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
XI (Optional)																							

* SDK: Software Development Kit **○: Special Firmware Required

* SDK: Software Development Kit **○: Special Firmware Required

NOTES

NOTES

YOUR PRINTING CHALLENGE SOLVED





BIXOLON
www.BIXOLON.com

BIXOLON Co.,Ltd.
+82 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Mexico
+521 55 8852 7880
marcelo@bixolonusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

BIXOLON MEA
+971 4 222 6480
russell@bixolon.com

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

September 2026