SPEC SHEET

SPP-R200III

2-inch Mobile Receipt Printer



Print Characteristics

Print Method
Direct Thermal
Print Speed
Up to 100 mm/sec (Receipt)
Up to 80 mm/sec (Linerless)
Print Resolution
203 dpi
Print Width
Up to 48 mm
Sensor
Paper End, Cover Open

Media Characteristics

Media Type
Standard: Receipt, Liner
Optional: Linerless
Media Width
Standard: 58 mm
Optional: Partition 50 mm
Media Roll Diameter
Up to 40 mm
Media Thickness
0.07 ± 0.005 mm

Physical Characteristics

Dimensions (W x L x H)
79.5 x 124.5 x 44.1 mm
(3.13 x 4.90 x 1.74 inch)
Weight
Including Battery: 228 g (0.50 lbs.)
Including MSR: 238 g (0.52 lbs.)
Power (Nominal Capacity)
EnergyStar® Certified, External AC/DC
SPP-R200III:
Battery (7.4 V Li-ion,
1200 mAh, Under 2.5 Hours Charging Time)

Performance Characteristics

Memory
8 MB SDRAM, 4 MB Flash
Interface
SPP-R200III
Standard: USB 2.0 FS + Serial
Optional:
① USB 2.0 FS + Serial + Bluetooth®
② USB 2.0 FS + Serial + WLAN

WLAN: 802.11a/b/g/n (Infrastructure,
Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104,
WPA1/2 (PSK, EAP)

Easy Bluetooth Pairing™ via NFC
Port
SPP-R200III: Power, Serial/USB 14P

Environment Characteristics

Temperature
Operating: -15 to 50°C (5 to 122°F)
Storage: -30 to 70°C (-22 to 158°F)
Humidity
Operating: 10 to 90% RH
Sealing
IP43 (IP54 with Protective Case)
Drop Rate
2.1 m (7 ft.)/1.5 m (5 ft.) for MSR Model

Software

Emulation
BXL/POS™
Driver/Utility
Windows® Driver, OPOS/JPOS Driver,
Linux®/macOS® CUPS Driver, Utility Program,
Network Auto Installer
Developer Tools
Android™/iOS®/Windows SDK,
Linux SDK, Xamarin® SDK,
Web Print SDK (Android/iOS/Windows/macOS),
Cordova™ Plugin, MAUI SDK, Flutter™ Plugin,
React Native® SDK
Design & Print
mPrint App (Android/iOS)

Fonts/Graphics/Symbologies

Character Size
Font A: 12 × 24 Font B: 9 × 17
Font C: 9 × 24, KOR, CHN, JPN: 24 × 24
Characters Per Line
Font A: 32
Font B, C: 42, KOR, CHN, JPN: 16
Character Sets
Alphanumeric: 95
Expanded Graphics: 128 × 33 Page
International: 32
Optional Unicode Supported
(UTF-8, UTF-16LE, UTF-16BE)
Barcode Symbologies
1D: Codabar, Code 39, Code 93,
Code 128, EAN-8, EAN-13, ITF,
UPC-A, UPC-E
2D: Aztec, Data Matrix, GS1 Databar,
MaxiCode, PDF417, QR Code

Accessories/Supplies

Included in the Box
Belt Clip, Battery, AC/DC Battery Charger,
Power Cord, Paper
Options & Accessories
Belt/Shoulder Strap, Soft/Protective Case,
Battery, USB Charger, Power Cord,
Single/Quad Battery Charger,
Single/Quad Docking Cradle,
Vehicle Charger, Vehicle Holder,
Serial Cable (D-Sub 9P(M)-14P,1 m),
USB Cable (A-14P,1 m),
Protective Jacket, Battery Clip
Compatible Supplies
B-linerless™

Integrated Card Reader (Optional)

MSR
3 Track (T-DES/DUKPT (Optional))

BIXOLON
www.BIXOLON.com

BIXOLON Co.,Ltd.
+82 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Mexico
+521 55 8852 7880
marcelo@bixolonmx.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

BIXOLON MEA
+971 4 222 6480
Russell@bixolon.com

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.