

LANDI

C20 Pro

Android Desktop POS
Terminal



**Future-ready SoftPOS power in an
all-in-one performance hub.**

- Enhance user perception with interactive design.
- Tackle peak hours with seamless and speedy printing.
- Empowered by LANDI Connect platform to unlock the full potential of digital commerce.
- Maximize counter flexibility with detachable CFD customer display.



SPECIFICATIONS

Processor	64-bit octa-core ARM Cortex	Ports	1*USB Type-C port 1*Micro USB port 4*USB Type-A 2.0 port 1*USB Type-A 3.0 port 1*RJ22 serial port 1*RJ45 Ethernet port 1*RJ11 cash drawer port 1*3.5 mm audio jack
Operating System	Android 13 (GMS)	NFC (Optional)	Android NFC, ISO/IEC 14443, ISO15693 compliant, Supports Type A/B Mifare, FeliCa (Optional) <i>*Only supported on the 10.1"/15.6" premium CFD</i>
Memory	Internal: 4GB RAM + 64GB FLASH 8GB RAM + 128GB FLASH (Optional) Expansion: MicroSD card, up to 2TB	SIM/SAM Slots (Optional)	1*SIM
Main Display	15.6", 1920 × 1080, capacitive multi-touch 178° viewing angle	Power	100V-240V AC, 50-60Hz input; 19V DC, 3.42A output
Customer-Facing Display	Option 1: None Option 2: 10.1" premium CFD (1280 × 800, touch panel, camera, NFC) Option 3: 15.6" premium CFD (1920 × 1080, touch panel, micro USB HOST, NFC)	Dimensions (L × W × H)	361.5 × 234 × 364 mm (Single display version) (Terminal only)
Buttons	1*Power button with indicator light 2*Volume button 1*Function button	Weight	4.4kg (Single display version) (Terminal only) 5kg (Dual display version) (Terminal only)
Camera	Front camera: 0.3MP, QR code scan (Optional) <i>*Only supported on the 10.1" premium CFD</i>	Operating Temp.	0°C to +40°C (32°F to 104°F)
Printer	Thermal printer Paper Width: 80 mm Roll Diameter: 80 mm Print Speed: 250 mm/s max Auto cutter	Storage Temp.	-20°C to +60°C (-4°F to 140°F)
Audio	5W, 100dB@1m, Dual speakers 1*Headset via 3.5mm audio jack (CTIA&OTMP) 2*Microphone	Operating Humidity	5% to 95% (Non-condensing)
Connectivity	WAN: 4G/3G/2G fallback (Optional) Wi-Fi: IEEE 802.11 a/b/g/n/ac, 2.4Ghz/5Ghz LAN: 1000 Mbps Bluetooth: Bluetooth 5.0, supports BLE	Certifications & Compliance	PCI:PCI MPoC Regulatory:CE, CB, FCC, IC, RoHS, WEEE, UN 38.3, DGM, GMS, ANATEL, PTCRB, NOM, CRT, BSMI, NCC
Positioning (Optional)	AGPS, GPS, GLONASS, BeiDou, Galileo (Optional)	Accessories (Sold separately)	C20 MSR C20 CAM HS20 Scanner DP20 Printer CD20 Cash Drawer

Rev. 2026.09.30



LANDi

C20 Pro SE

Android Desktop POS
Terminal



**Future-ready SoftPOS power in an
all-in-one performance hub.**

www.landiglobal.com

- Enhance user perception with interactive design.
- Empowered by LANDI Connect platform to unlock the full potential of digital commerce.
- Maximize counter flexibility with detachable CFD customer display.



SPECIFICATIONS

Processor	64-bit octa-core ARM Cortex	Ports	1*USB Type-C port 1*Micro USB port 4*USB Type-A 2.0 port 1*USB Type-A 3.0 port 1*RJ22 serial port 1*RJ45 Ethernet port 1*RJ11 cash drawer port 1*3.5 mm audio jack
Operating System	Android 13 (GMS)	Dimensions (L x W x H)	361.5 x 234 x 364 mm (Single display version) (Terminal only)
Memory	Internal: 4GB RAM + 64GB FLASH 8GB RAM + 128GB FLASH (Optional) Expansion: MicroSD card, up to 2TB	Weight	3.9kg (Single display version) (Terminal only) 4.5kg (Dual display version) (Terminal only)
Main Display	15.6", 1920 x 1080, capacitive multi-touch 178° viewing angle	Power	100V-240V AC, 50-60Hz input; 19V DC, 3.42A output
Customer-Facing Display	Option 1: None Option 2: 10.1" premium CFD (1280 x 800, touch panel, camera, NFC) Option 3: 15.6" premium CFD (1920 x 1080, touch panel, micro USB HOST, NFC)	Operating Temp.	0°C to +40°C (32°F to 104°F)
Buttons	1*Power button with indicator light 2*Volume button 1*Function button	Storage Temp.	-20°C to +60°C (-4°F to 140°F)
Camera	Front camera: 0.3MP, QR code scan (Optional) <i>*Only supported on the 10.1" premium CFD</i>	Operating Humidity	5% to 95% (Non-condensing)
Audio	5W, 100dB@1m, Dual speakers 2*Microphone 1*Headset via 3.5mm audio jack (CTIA&OTMP)	Certifications & Compliance	CE, CB, FCC, IC, RoHS, WEEE, UN 38.3, DGM, GMS, ANATEL
Connectivity	Wi-Fi: IEEE 802.11 a/b/g/n/ac, 2.4Ghz/5Ghz LAN: 1000 Mbps Bluetooth: Bluetooth 5.0, supports BLE	Accessories (Sold separately)	C20 MSR C20 CAM HS20 Scanner DP20 Printer CD20 Cash Drawer
NFC (Optional)	Android NFC, ISO/IEC 14443, ISO15693 compliant, Supports Type A/B Mifare, FeliCa(Optional) <i>*Only supported on the 10.1"/15.6" premium CFD</i>		

Rev. 2026.09.30

LANDI

This document is not binding and the specifications above can be modified without prior consent.

