

P10 Countertop

Android payment terminal



*5.5-inch display shown

Design to what matters

Designing smarter to deliver more - for less.

Built with cost-conscious businesses in mind, LANDI P10 Countertop delivers exactly what matters: seamless transactions, essential features and intuitive design - without the extras you don't need.

Countertop efficiency

Stable, connected and ready for everyday business.

Designed for fixed checkout environments, LANDI P10 Countertop combines reliable connectivity, enhanced memory options and dependable performance to keep transactions flowing smoothly throughout the day.

Built to last

Ready for the future, Built on proven foundations.

Engineered for long-term performance, LANDI P10 Countertop is PCI PTS 7.x and Android 14 - offering extended lifecycle support and peace of mind in every transaction.



SPECIFICATIONS

Processor	Qualcomm 64-bit quad-core ARM Cortex-A53, 2.0 GHz	Camera	Front camera: 0.3MP with fixed focus (for barcode scanning) 2MP with fixed focus (for barcode scanning) (Optional)
System	Android 14 (32 bits)		
Memory	Internal: 2GB RAM + 8GB FLASH 2GB RAM + 32GB FLASH (Optional) Expansion: MicroSD card, up to 2TB		
Display	5", 480×854, capacitive multi-touch 5.5", 720×1440, capacitive multi-touch (Optional)	SIM/SAM Slots	2*SAM 1*SIM + 3*SAM (Optional) 1*SIM + 1*eSIM + 2*SAM (Optional)
Printer	Thermal printer Paper width: 58 mm Roll diameter: 40 mm Print speed: 100 mm/s max	Ports	1*USB Type-A Host port 1*USB Type-C Device port 1*RJ45 Ethernet port 1*RJ22 Serial port
Button	Physical: Power, Menu, Home, Back (For the 5" main display version) Physical: Power; Virtual: Menu, Home, Back (For the 5.5" main display version) (Optional)	Power	Supply: 100-240V AC 50/60Hz input; 9.0V DC, 2.5A output
Audio	1*Speaker 1*Buzzer (Optional) 1*Headset via USB Type-C port (Optional) 1*Microphone (Optional)	Dimensions (L × W × H)	197 × 82 × 70 mm (Terminal only)
Vibration	Vibration (Optional)	Weight	402g (Terminal only)
Connectivity	WAN: 4G/3G/2G fallback (Optional) Wi-Fi: IEEE 802.11 a/b/g/n/ac, 2.4Ghz/5Ghz LAN: 10/100 Mbps Bluetooth: Bluetooth 5.0, supports BLE	Operating Temperature	-10°C to +50°C (14°F to 122°F)
Card Reader	Mag Card: ISO 1/2/3 track, bi-directional Smart Card: EMV Contact L1 & L2, ISO 7816 Contactless: EMV Contactless L1 & L2, ISO/IEC 14443 Type A/B, MIFARE, FeliCa 4*LED status indicator	Storage Temperature	-20°C to +70°C (-4°F to 158°F)
		Operating Humidity	5% to 95% (Non-condensing)
		Accessories (Sold separately)	Add-on keypad for visually impaired users
		Certifications	PCI: PCI PTS 7.x Payment: EMVCo Contact L1 & L2, EMVCo Contactless L1 & L2, Mastercard PayPass, Visa payWave, JCB, UPI qUICS, Amex ExpressPay, Discover D-PAS, TQM, PURE, RuPay, CPACE Regulatory: CE, CB, FCC, IC, RoHS, UN 38.3, DGM, WEEE

Rev. 2026.09.30



P10 Wireless

Android payment terminal

Qualcomm Platform



Design to what matters

Designing smarter to deliver more - for less.

Built with cost-conscious businesses in mind, LANDi P10 Wireless delivers exactly what matters: seamless transactions, essential features and intuitive design - without the extras you don't need.

Flexible deployment

One terminal, endless possibilities.

With full wireless functionality, LANDi P10 Wireless adapts to your environment with ease - delivering reliable performance in a setup that fits your business.

Built to last

Ready for the future, Built on proven foundations.

Engineered for long-term performance, LANDi P10 Wireless device is PCI PTS 7.x and Android 14 - offering extended lifecycle support and peace of mind in every transaction.



SPECIFICATIONS

Processor	Qualcomm 64-bit quad-core ARM Cortex-A53, 2.0 GHz	Card Reader	Mag Card: ISO 1/2/3 track, bi-directional Smart Card: EMV Contact L1 & L2, ISO 7816 Contactless: EMV Contactless L1 & L2, ISO/IEC 14443 Type A/B, MIFARE, FeliCa 4*LED status indicator
OS	Android 14 (32 bits)	SAM/SIM slots	2 SIM + 2 SAM 1 SIM + 3 SAM (Optional) 1 SIM + 1 eSIM + 2 SAM (Optional)
Memory	Internal: 2GB RAM + 8GB FLASH 2GB RAM + 16GB FLASH (Optional) 2GB RAM + 32GB FLASH (Optional) External: MicroSD card, up to 2TB	Connection	1*USB Type-C port 2*Pogo pin
Main Display	5", 480×854, capacitive multi-touch 5.5", 720×1440, capacitive multi-touch (Optional)	Power (Battery Version)	Supply: 100-240V AC 50/60Hz input; 5.0V DC, 2.0A output Battery: 7.2V 2600mAh / 18.72Wh (equivalent to 3.6V 5200mAh), removable; 7.2V 3350mAh / 24.12Wh (equivalent to 3.6V 6700mAh), removable (Optional)
CFD	Display & Touchscreen 2", 240×320, non-touch (Optional) Camera 0.3MP with fixed focus (for barcode scanning) (Optional)	Dimensions (L × W × H)	197 × 82 × 63 mm (Terminal only)
Printer	Thermal printer Paper width: 58 mm Roll diameter: 40 mm Print speed: 100 mm/s max	Weight	346g (Terminal only)
Keys	Physical: Power, Menu, Home, Back (For the 5" main display version) Physical: Power; Virtual: Menu, Home, Back (For the 5.5" main display version) (Optional)	Operating Temperature	Discharging: -10°C to +50°C (14°F to 122°F) Charging: 0°C to +40°C (32°F to 104°F)
Audio	1*Speaker 1*Buzzer (Optional) 1*Headset via USB Type-C port (Optional) 1*Microphone (Optional)	Storage Temperature	-20°C to +70°C (-4°F to 158°F)
Vibration	Vibration (Optional)	Operating Humidity	5% to 95% (Non-condensing)
Connectivity	WAN: 4G/3G/2G fallback Wi-Fi: IEEE 802.11 a/b/g/n/ac, 2.4Ghz/5Ghz Bluetooth: Bluetooth 5.0, supports BLE	Accessories (Optional)	Charging base Functional base Add-on keypad for visually impaired users
Camera	Front camera: 0.3MP with fixed focus (for barcode scanning) 2MP with fixed focus (for barcode scanning) (Optional) Rear camera: 0.3MP with fixed focus (for barcode scanning) 5MP with autofocus & flash (Optional)	Certification	PCI: PCI PTS 7.x Payment: EMVCo Contact L1 & L2, EMVCo Contactless L1 & L2, Mastercard PayPass, Visa payWave, JCB, UPI qUICS, Amex ExpressPay, Discover D-PAS, TQM, PURE, RuPay, CPACE Regulatory: CE, CB, FCC, IC, RoHS, WEEE, UN 38.3, DGM, MTC
Positioning	GPS, GLONASS, BeiDou, Galileo		

Rev. 2026.09.30



P10 Wireless

Android payment terminal

Unisoc Platform



Design to what matters

Designing smarter to deliver more - for less.

Built with cost-conscious businesses in mind, LANDI P10 Wireless delivers exactly what matters: seamless transactions, essential features and intuitive design - without the extras you don't need.

Flexible deployment

One terminal, endless possibilities.

With full wireless functionality, LANDI P10 Wireless adapts to your environment with ease - delivering reliable performance in a setup that fits your business.

Built to last

Ready for the future, Built on proven foundations.

Engineered for long-term performance, LANDI P10 Wireless device is Android 12 - offering extended lifecycle support and peace of mind in every transaction.



SPECIFICATIONS

Processor	Unisoc 64-bit quad-core ARM Cortex-A53, 1.4 GHz	Card Reader	Mag Card: ISO 1/2/3 track, bi-directional Smart Card: EMV Contact L1 & L2, ISO 7816 Contactless: EMV Contactless L1 & L2, ISO/IEC 14443 Type A/B, MIFARE, FeliCa 4*LED status indicator
OS	Android 12 (32 bits)	SAM/SIM slots	2 SIM + 2 SAM 1 SIM + 3 SAM (Optional) 1 SIM + 1 eSIM + 2 SAM (Optional)
Memory	Internal: 1GB RAM + 8GB FLASH 2GB RAM + 16GB FLASH (Optional) External: MicroSD card, up to 2TB	Connection	1*USB Type-C port 2*Pogo pin
Main Display	5", 480×854, capacitive multi-touch 5.5", 720×1440, capacitive multi-touch (Optional)	Power (Battery Version)	Supply: 100-240V AC 50/60Hz input; 5.0V DC, 2.0A output Battery: 7.2V 2600mAh / 18.72Wh (equivalent to 3.6V 5200mAh), removable; 7.2V 3350mAh / 24.12Wh (equivalent to 3.6V 6700mAh), removable (Optional)
CFD	2", 240×320, non-touch (Optional)	Dimensions (L × W × H)	197 × 82 × 63 mm (Terminal only)
Printer	Thermal printer Paper width: 58 mm Roll diameter: 40 mm Print speed: 100 mm/s max	Weight	346g (Terminal only)
Keys	Physical: Power, Menu, Home, Back (For the 5" main display version) Physical: Power; Virtual: Menu, Home, Back (For the 5.5" main display version) (Optional)	Operating Temperature	Discharging: -10°C to +50°C (14°F to 122°F) Charging: 0°C to +40°C (32°F to 104°F)
Audio	1*Speaker 1*Buzzer (Optional) 1*Headset via USB Type-C port (Optional) 1*Microphone (Optional)	Storage Temperature	-20°C to +70°C (-4°F to 158°F)
Vibration	Vibration (Optional)	Operating Humidity	5% to 95% (Non-condensing)
Connectivity	WAN: 4G/3G/2G fallback Wi-Fi: IEEE 802.11 b/g/n, 2.4Ghz IEEE 802.11 a/b/g/n/ac, 2.4Ghz/5Ghz (Optional) Bluetooth: Bluetooth 4.2, supports BLE (For 2.4G Wi-Fi module) Bluetooth 5.0, supports BLE (For dual Wi-Fi module) (Optional)	Accessories (Optional)	Charging base Functional base Add-on keypad for visually impaired users
Positioning	GPS, GLONASS, BeiDou, Galileo	Certification	PCI: PCI PTS 7.x Payment: EMVCo Contact L1 & L2, EMVCo Contactless L1 & L2, Mastercard PayPass, Visa payWave, JCB, UPI qUICS, Amex ExpressPay, Discover D-PAS, TQM, PURE, RuPay Regulatory: CE, CB, FCC, RoHS, WEEE, UN 38.3, DGM, BIS, WPC, DJID, NBTC
Camera	Front camera: 0.3MP with fixed focus (for barcode scanning) 2MP with fixed focus (for barcode scanning) (Optional) Rear camera: 0.3MP with fixed focus (for barcode scanning) 5MP with autofocus & flash (Optional)		

Rev. 2026.09.30

LAUDI

This document is not binding and the specifications above can be modified without prior consent.

