

Imager 2D con supporto regolabile

Montato a parete, posizionato su una scrivania o in posizione fissa ad angolo regolato per la scansione a mani libere.





MS339

Imager 2D robusto e conveniente

Unitech MS339 è progettato per soddisfare tutte le esigenze di scansione dei barcodes a un prezzo accessibile.

Questo scanner ad alte prestazioni, legge tutti i comuni codici a barre 1D e 2D, anche se stampati male o su etichette danneggiate, e barcodes digitali da display mobili (compresi i codici QR) su vari tipi di display per migliorare i livelli di servizio.

La luce ausiliaria bianca soft e il puntatore verde offrono un'esperienza di scansione comoda e appropriata. Il design elegante ed ergonomico fa sì che l'MS339 si adatti comodamente a qualsiasi mano, riducendo l'affaticamento durante le attività di scansione di lunga durata

L'MS339 viene fornito all-in-one con 5 anni di garanzia!

L'MS339 è perfetto per tutti i tipi di vendita al dettaglio e per uso aziendale. La sua semplice configurazione plug-and-play garantisce una facile integrazione nella gestione unica di tutti i processi lavorativi.

Caratteristiche

- L'MS339 viene fornito con un cavo USB a spirale da 2,4 m, supporto hands-free e 5 anni di garanzia per la sostituzione
- Prestazioni scattanti
- Velocità di decodifica 600 volte al secondo
- Supporto regolabile: montaggio su scrivania, a parete o in posizione di scansione a mani libere regolabile.
- Supporta USB/HID, USB/SPP, RS232 e OPOS
- Legge barcodes stampati male e da schermi mobili
- Design ergonomico e impugnatura comoda
- Supporta la modalità Trigger e Auto-sensing
- Design durevole: test di caduta da 2,0 metri e grado di protezione IP52

unitech
because we care



IT v1.2 MS339 Specifications

Operational & Performance

Receiving Device	Imager sensor, 1280 x 800 pixels
Scan Skew	± 70°
Scan Pitch	± 75°
Scan Roll	360°
Motion Tolerance	1.5m/s.
Immunity:	100.000 lux
Light Source	Illumination: 5000K, white LED. Aiming: 525 nm peak wavelenght, green LED.
Field of view	Horizontal 41° / Vertical 28°
Decoding Rate	600 times per second
Indicator	Beep, LED
Interface	USB/HID, USB/SPP, RS232 and OPOS* (additional software driver needed)

Reading distance (DOF)

Depth of Field*

1D: 0mm to 340mm

2D: 0mm to 340m

5mil Code39 (3 chars):	5 - 115
10mil Code39 (3 chars):	0 - 250
13mil UPC (6 chars):	15 - 340
20mil Code39 (5 chars):	15 - 340
6.7mil PDF417 (20 chars):	10 - 100
10mil QR (20 chars):	0 - 155
10mil DM (20 chars):	0 - 160
20mil QR (20 chars):	0 - 270

* = dependents on width of barcode

Symbologies

1D: UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128, ISBT 128, Code 93, Code 11 (USD-8), MSI/ Plessey, UK/Plessey, China Post, China Finance, Telepen, GS1 DataBar (formerly RSS) variants and TLC-39 postal code.

2D: PDF417, QR Code, Data Matrix, Han Xin, Code, Aztec Code, MicroQR Code, MicroPDF417, **MaxiCode**.

Power Source

Operation Voltage	5 VDC ± 0.25 V
Power consumption:	Standby: 1600 mA Working: 300 mA

Material

Case material:	PC + TPU
Exit window material:	Tempered glass

Enclosure

Scanner dimension	90mm x 62.8mm x 153mm
Scanner weight	132g (without cable)
Cable	2.4m coiled cable

Environmental

Mechanical Shock	Withstands multiple 2.0m drops to concrete.
IP Rating	IP52
Operating Temperature	-10°C to 50°C
Storage Temperature	-20°C to 70°C
Relative Humidity	5% to 95% non-condensing

Operation modes

Trigger, auto-sensing

Connectivity

USB cable

Safety & EMC

Photobiological Safety:	EN62471
EMC:	EN55032
ESD Protection:	EN61000-4-2
RF Immunity:	IEC61000-4-3, 10 V/m

Regulator approvals

CE, FCC

Warranty

5 Years scanner only*
1 Year USB cable

Unitech Europe
Tilburg, The Netherlands
- Tel.: +31 (0)13 460 9292
- Email: Info@eu.ute.com
- Website: http://eu.ute.com

unitech
because we care

Unitech America | Unitech Asia Pacific | Unitech China | Unitech Europe | Unitech Japan | Unitech Taiwan

* Warranty: Unitech reserves the right to call back the defect units at her discrete sole decision if Unitech may find it necessarily. Upon the calling, the returning shipping cost will be borne by Unitech except tax and duty if any. Unitech has full decision to stop the warranty coverage before expiration if the defect is found due to abused, sabotage, and/or caused by the acts of God Specifications subject to change without notice.

Copyright 2011 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.