Newland AIDC
SCANNING MADE SIMPLE



# NLS-WCD10-1C
# Charging Cradle for WD1

Base Stations



## Features

**Professional and Reliable Design.**
The cradle has a simple and reliable design, which helps to fit the WD1 Wearable Scanner perfectly into the charging slot. The cradle ensures that WD1 is in good contact and stable charging.

**Simultaneous Charging for Multi-terminals.**
Each cradle can support one WD1 charging at the same time. A maximum of five cradles can be linked.

**1** Year Full Warranty

TECHNICAL SPECIFICATIONS

## NLS-WCD10-1C Charging Cradle for WD1

### Physical

| | |
|---|---|
| AC Adapter | DC 19V 3.2A for spliced cradles |
| Dimensions | 90(L)*70(W)*37(H) mm |
| Expected Charge Time | WD1≤3.5H（DC 19V 3.2A） |
| Notifications | LED |
| Weight | 170g |

### Environmental

| | |
|---|---|
| Drop | 1.0m drops to concrete (for six sides, one drop per side) |

| | |
|---|---|
| Electro Static Discharge (ESD) | ±12 kV (air discharge), ±8 kV (direct discharge) |
| Humidity | 5% to 95% (non-condensing) |
| IP Rating | IP30 |
| Operating Temperature | 5°C to 45°C (-32°F to 113°F) |
| Storage Temperature | -30°C to 60°C (-22°F to 140°F) |

## Warranty

| | |
|---|---|
| Warranty Standard | 1 Year |

Newland AIDC EMEA
SCANNING MADE SIMPLE

**Newland AIDC EMEA**
Feel free to contact us or a partner near you.
info@newland-id.com - newland-id.com

Specifications are subject to change without notice
© Newland AIDC EMEA 2026 - All rights reserved